


INDUSTRIAL COMPONENT DATA

3KC8456-0JA22-0GA3 SIEMENS SENTRON, ATE, transfer switching equipment 3KC, automatically, ATSE, 4- pole, lu:..

Brand: SIEMENS | Manufacturer Part Number: 3KC8456-0JA22-0GA3



Manufacturer	SIEMENS
MPN / Reference	3KC8456-0JA22-0GA3
Catalog number	84560
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-99C06CD5D4
Generated	2026-08-02

Product Overview

SENTRON, ATE, transfer switching equipment 3KC, automatically, ATSE, 4- pole, lu: 2000 A, Ue AC: 415 V, Ie at AC-33 B at 415 V: 1250 A, screw mounting, motorized operating mechanism, at the right end, long handle, busbar connection TRANSF SWITCH. AUTOMATIC ATSE, 2000A, 4 POLES FRONT DRIVE BASE UNIT WITH LEVER 2X POWER 230VAC FLAT CONNECTIONS. Cancellations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > 3KD Switch-disconnectors, 3KC Pow

Additional Product Information

ETIM: EC000216 - Switch disconnecter

Value Unit

Rated permanent current at AC-23, 400 V (EF011777) - A

Degree of protection (NEMA) (EF011959) -

Version as main switch (EF006981) true

Version as maintenance-/service switch (EF006986) true

Version as safety switch (EF006985) true

Version as emergency stop installation (EF006959) false

Version as reversing switch (EF009408) -

Number of switches (EF005586) -

Max. rated operation voltage Ue AC (EF007355) 415 V

Rated operating voltage (EF001435) ['166.0', '332.0'] V

Rated permanent current I_u (EF001389) 2000.0 A
Rated permanent current at AC-21, 400 V (EF009165) - A
Rated short-time withstand current I_{cw} (EF007050) 50.0 kA
Number of poles (EF001391) 4
Number of auxiliary contacts as normally closed contact (EF001377) 0
Number of auxiliary contacts as normally open contact (EF001376) 0
Number of auxiliary contacts as change-over contact (EF003531) 0
Motor drive optional (EF007386) false
Motor drive integrated (EF006697) true
Voltage release optional (EF007491) false
Device construction (EF008240) Built-in device fixed built-in technique
Suitable for floor mounting (EF007243) FALSE
Suitable for front mounting 4-hole (EF007247) false
Suitable for front mounting centre (EF007248) false
Suitable for distribution board installation (EF007262) false
Suitable for intermediate mounting (EF007264) false
Colour control element (EF007167) Black
Type of control element (EF006976) Long turning handle
Interlockable (EF006281) true
Type of electr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3KC8456-0JA22-0GA3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.