

INDUSTRIAL COMPONENT DATA

3KD2644-2ME40-0 SIEMENS Switch disconnecter 63 A, Size 1, 4-pole Lateral operating mechanism right Basic uni..

Brand: SIEMENS | Manufacturer Part Number: 3KD2644-2ME40-0



Manufacturer	SIEMENS
MPN / Reference	3KD2644-2ME40-0
Catalog number	26442
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-D514D5F8EB
Generated	2026-08-03

Product Overview

Switch disconnecter 63 A, Size 1, 4-pole Lateral operating mechanism right Basic unit without handle Box terminal
SWITCH-DISCONNECTOR 63A, SIZE 1, 4 POLES ACCTO. RIGHT SIDE. BASE UNIT WITHOUT HANDLE FRAME
TERMINALS.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > 3KD Switch-disconnectors, 3KC Pow

Additional Product Information

ETIM: EC000216 - Switch disconnecter

Value Unit

Degree of protection (NEMA) (EF011959) -

Number of switches (EF005586) -

Rated permanent current at AC-23, 400 V (EF011777) - A

Rated operating voltage (EF001435) - V

Version as main switch (EF006981) true

Version as maintenance-/service switch (EF006986) true

Version as safety switch (EF006985) true

Version as emergency stop installation (EF006959) true

Version as reversing switch (EF009408) false

Max. rated operation voltage Ue AC (EF007355) 690 V

Rated permanent current Iu (EF001389) 63.0 A

Rated permanent current at AC-21, 400 V (EF009165) 63 A
Rated operation power at AC-23, 400 V (EF007027) 30.0 kW
Switching power at 400 V (EF009166) 30.0 kW
Number of poles (EF001391) 4
Number of auxiliary contacts as normally closed contact (EF001377) 0
Number of auxiliary contacts as normally open contact (EF001376) 0
Number of auxiliary contacts as change-over contact (EF003531) 3
Motor drive optional (EF007386) false
Motor drive integrated (EF006697) false
Voltage release optional (EF007491) false
Device construction (EF008240) Built-in device fixed built-in technique
Suitable for floor mounting (EF007243) FALSE
Suitable for front mounting 4-hole (EF007247) false
Suitable for front mounting centre (EF007248) false
Suitable for distribution board installation (EF007262) true
Suitable for intermediate mounting (EF007264) true
Colour control element (EF007167) Other
Type of control element (EF006976) None
Interlockable (EF006281) false
T...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3KD2644-2ME40-0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.