

INDUSTRIAL COMPONENT DATA

3KD3240-2NE10-0 SIEMENS Switch disconnecter 125 A, Size 2, 4-pole Front operating mechanism left Basic unit ..

Brand: SIEMENS | Manufacturer Part Number: 3KD3240-2NE10-0



Manufacturer	SIEMENS
MPN / Reference	3KD3240-2NE10-0
Catalog number	32402
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-CDF09D6F99
Generated	2026-08-03

Product Overview

Switch disconnecter 125 A, Size 2, 4-pole Front operating mechanism left Basic unit without handle Box terminal
SWITCH-DISCONNECTOR 125A, SIZE 2, 4 POLES ACCTO. FRONT TO LEFT. BASE UNIT WITHOUT LEVER FRAME
TERMINALS

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > 3KD Switch-disconnectors, 3KC Pow

Additional Product Information

Technical data

Switch disconnecter 125 A, Size 2, 4-pole Front operating mechanism left Basic unit without handle Box terminal

Model

product brand name SENTRON

product designation 3KD switch disconnecter

design of the product Switch

display version / for switch position indicator door-coupling rotary operating mechanism ON-OFF

design of the actuating element Without handle

type of the driving mechanism Front operating mechanism

type of the driving mechanism / motor drive No

General technical data

number of poles 4

type of device fixed mounting

size of switch disconnecter 2
mechanical service life (switching cycles) / typical 15 000
electrical endurance (switching cycles)
? at AC-23 A / at 690 V 1 500
? at DC-23 A / at 440 V 1 000
I_{2t} value
? with closed switch / at 1000 V / for combination switch +gG/aM SITOR fuse / maximum 19 815 A²·s
? of the fuse / at 500 V / maximum permissible 223 005 A²·s
? of the gG fuse / at 690 V / maximum permissible 226 005 A²·s
? of the gG/aM SITOR fuse / at 1000 V / maximum permissible 48 000 A²·s
? of the molded case circuit breaker / at 415 V / maximum permissible 560 000 A²·s
position / of the switch operating mechanism at the left end
overvoltage in percent / relative to the operating voltage / at AC / at 400, 500, 690 V / at 50/60 Hz 10 %
overvoltage category III
degree of pollution 3
Voltage
operating voltage / with current paths in series
? with degree of pollution 2 / at DC / rated value 440 V / 3
? with degree of pollution 3 / at DC / r...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3KD3240-2NE10-0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.