

INDUSTRIAL COMPONENT DATA

3KD3644-0NE10-0 SIEMENS Switch disconnecter 200 A, Size 2, 4-pole Lateral operating mechanism left Basic uni..

Brand: SIEMENS | Manufacturer Part Number: 3KD3644-0NE10-0



Manufacturer	SIEMENS
MPN / Reference	3KD3644-0NE10-0
Catalog number	36440
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-9CA98E37E7
Generated	2026-08-01

Product Overview

Switch disconnecter 200 A, Size 2, 4-pole Lateral operating mechanism left Basic unit without handle flat terminal incl. phase barriers

SWITCH-DISCONNECTOR 200A, SIZE 2, 4 POLES ACCTO. SIDE TO LEFT. BASE UNIT WITHOUT LEVER FLAT CONNECTIONS INCL. SEPARATOR WALLS PHASES

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > 3KD Switch-disconnectors, 3KC Pow

Additional Product Information

Technical data

Switch disconnecter 200 A, Size 2, 4-pole Lateral operating mechanism left Basic unit without handle flat terminal incl. phase barriers

Model

product brand name SENTRON

product designation 3KD switch disconnecter

design of the product Switch

display version / for switch position indicator door-coupling rotary operating mechanism ON-OFF

design of the actuating element Without handle

type of the driving mechanism Side operating mechanism

type of the driving mechanism / motor drive No

General technical data

number of poles 4
type of device fixed mounting
size of switch disconnecter 2
mechanical service life (switching cycles) / typical 15 000
electrical endurance (switching cycles)
? at AC-23 A / at 690 V 1 500
? at DC-23 A / at 440 V 1 500
I_{2t} value
? with closed switch / at 1000 V / for combination switch +gG/aM SITOR fuse / maximum 19 815 A²·s
? of the fuse / at 500 V / maximum permissible 780 005 A²·s
? of the gG fuse / at 690 V / maximum permissible 525 005 A²·s
? of the gG/aM SITOR fuse / at 1000 V / maximum permissible 48 000 A²·s
? of the molded case circuit breaker / at 415 V / maximum permissible 1 750 000 A²·s
position / of the switch operating mechanism at the left end
overvoltage in percent / relative to the operating voltage / at AC / at 400, 500, 690 V / at 50/60 Hz 10 %
overvoltage category III
degree of pollution 3
Voltage
operating voltage / with current paths in series
? with degree of pollution 2 / at DC / rated value 440 V / 3
? with degree o...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3KD3644-0NE10-0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.