

INDUSTRIAL COMPONENT DATA

3KD4232-0PE10-0 SIEMENS Switch disconnecter 400 A, Size 3, 3-pole Front operating mechanism left Complete un..

Brand: SIEMENS | Manufacturer Part Number: 3KD4232-0PE10-0



Manufacturer	SIEMENS
MPN / Reference	3KD4232-0PE10-0
Catalog number	42320
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-A6965D38EA
Generated	2026-07-29

Product Overview

Switch disconnecter 400 A, Size 3, 3-pole Front operating mechanism left Complete unit with direct operating mechanism gray flat terminal

SWITCH-DISCONNECTOR 400A, SIZE 3, 3 POLES ACCTO. FRONT TO LEFT. COMPLETE UNIT WITH ACCTO. FULL, GREY FLAT CONNECTION

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > 3KD Switch-disconnectors, 3KC Pow

Additional Product Information

Technical data

Switch disconnecter 400 A, Size 3, 3-pole Front operating mechanism left Complete unit with direct operating mechanism gray flat terminal

Model

product brand name SENTRON

product designation 3KD switch disconnecter

design of the product Switch

display version / for switch position indicator manual operation ON-OFF-TEST

design of the actuating element Long rotary knob

type of the driving mechanism Front operating mechanism

type of the driving mechanism / motor drive No

General technical data

number of poles 3
type of device fixed mounting
size of switch disconnecter 3
mechanical service life (switching cycles) / typical 15 000
electrical endurance (switching cycles)
? at AC-23 A / at 690 V 1 000
? at DC-23 A / at 440 V 1 000
I²t value
? with closed switch / at 1000 V / for combination switch +gG/aM SITOR fuse / maximum 239 650 A²·s
? of the fuse / at 500 V / maximum permissible 2 150 005 A²·s
? of the gG fuse / at 690 V / maximum permissible 1 650 005 A²·s
? of the gG/aM SITOR fuse / at 1000 V / maximum permissible 260 000 A²·s
? of the molded case circuit breaker / at 415 V / maximum permissible 4 750 000 A²·s
position / of the switch operating mechanism at the left end
overvoltage in percent / relative to the operating voltage / at AC / at 400, 500, 690 V / at 50/60 Hz 10 %
overvoltage category IV
degree of pollution 3
Voltage
operating voltage / with current paths in series
? with degree of pollution 2 / at DC / rated value 440 V / 3
? with degree of polluti...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3KD4232-0PE10-0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.