

## INDUSTRIAL COMPONENT DATA

# 3KE4330-0BA SIEMENS switch disconnecter, 3-pole I 400A, U 690V front mounted rotary operator with black hand..

Brand: SIEMENS | Manufacturer Part Number: 3KE4330-0BA



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | SIEMENS             |
| MPN / Reference | 3KE4330-0BA         |
| Catalog number  | 43300               |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-732479D412       |
| Generated       | 2026-08-02          |

## Product Overview

switch disconnecter, 3-pole I=400A, U=690V front mounted rotary operator with black handle

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path SIEMENS &gt; POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR &gt; SWITCHES-DISCONNECTORS

## Additional Product Information

ETIM: EC000216 - Switch disconnecter

Value Unit

Rated short-time withstand current I<sub>cw</sub> (EF007050) - kA

Version as reversing switch (EF009408) -

Number of switches (EF005586) -

Switching power at 400 V (EF009166) - kW

Degree of protection (NEMA) (EF011959) -

Rated permanent current at AC-21, 400 V (EF009165) - A

Rated operating voltage (EF001435) - V

Colour control element (EF007167) -

Version as main switch (EF006981) true

Version as maintenance-/service switch (EF006986) true

Version as safety switch (EF006985) true

Version as emergency stop installation (EF006959) true

Max. rated operation voltage U<sub>e</sub> AC (EF007355) 690 V

Rated permanent current I<sub>u</sub> (EF001389) 400.0 A  
Rated permanent current at AC-23, 400 V (EF011777) 400 A  
Conditioned rated short-circuit current I<sub>q</sub> (EF001444) 50.0 kA  
Number of poles (EF001391) 3  
Number of auxiliary contacts as normally closed contact (EF001377) 0  
Number of auxiliary contacts as normally open contact (EF001376) 0  
Number of auxiliary contacts as change-over contact (EF003531) 0  
Motor drive optional (EF007386) false  
Motor drive integrated (EF006697) false  
Voltage release optional (EF007491) false  
Device construction (EF008240) Built-in device fixed built-in technique  
Suitable for floor mounting (EF007243) FALSE  
Suitable for front mounting 4-hole (EF007247) false  
Suitable for front mounting centre (EF007248) false  
Suitable for distribution board installation (EF007262) false  
Suitable for intermediate mounting (EF007264) false  
Type of control ele...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3KE4330-0BA with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.