

INDUSTRIAL COMPONENT DATA

3KF1308-4RB11 SIEMENS Switch disconnecter with fuse 80 A, Size 1, 3-pole for LV HRC fuse Sz. 000 Side operat..

Brand: SIEMENS | Manufacturer Part Number: 3KF1308-4RB11



Manufacturer	SIEMENS
MPN / Reference	3KF1308-4RB11
Catalog number	13084
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-EE01CE098D
Generated	2026-08-06

Product Overview

Switch disconnecter with fuse 80 A, Size 1, 3-pole for LV HRC fuse Sz. 000 Side operating mechanism right Basic unit without handle Box terminal

INTERR.-DISCONNECTOR W/FUSES 80A, SIZE 1, 3 POLES FOR NH TAM FUSES. 000 ACCTO. SIDE WALL RIGHT. BASE UNIT WITHOUT HANDLE BOX TERMINALS. Cancellations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > SWITCHES-DISCONNECTORS

Additional Product Information

Technical data

Switch disconnecter with fuse 80 A, Size 1, 3-pole for LV HRC fuse Sz. 000 Side operating mechanism right Basic unit without handle Box terminal

Model

product brand name SENTRON

design of the product 3KF switch disconnecter with fuses

product variations 3KF NH

design of the actuating element without

design of handle Without

direction of actuation from right

type of the driving mechanism / motor drive No

number of poles 3

size of disconnecting link 00 and 000

size of switch disconnecter 1

size of fuse link NH000, NH00

mechanical service life (switching cycles) / typical 15 000

electrical endurance (switching cycles)

? at AC-23 A / at 440 V 10 000

? at AC-23 A / at 690 V 6 000

? at DC-23 A / at 440 V 1 500

I²t value

? with closed switch / for combination switch + fuse / at 500 V / maximum 33 200 A²·s

? with closed switch / for combination switch + fuse / at 400 V / maximum 33 200 A²·s

? with closed switch / at 690 V / for combination switch + gG fuse / maximum 40 700 A²·s

? of the fuse / at 500 V / maximum permissible 34 000 A²·s

? of the gG fuse / at 690 V / maximum permissible 55 000 A²·s

? of the aM fuse / at 690 V / maximum permissible 55 000 A²·s

fuse system LV HRC fuse

overvoltage category IV

operating voltage / with current paths in series

? with degree of pollution 2 / at DC / rated value 440 / 3

? with degree of pollution 3 / at DC / rated value 440 / 3

surge voltage resistance / rated value 12 kV

Supply voltage

operating voltage / at AC / rated value /...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3KF1308-4RB11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.