

INDUSTRIAL COMPONENT DATA

3KL5030-1AG01 SIEMENS Switch disconnecter with fuse in new design lu 63 A, Ue 690 V, 3-pole for BS88 fuse fo..

Brand: SIEMENS | Manufacturer Part Number: 3KL5030-1AG01



Manufacturer	SIEMENS
MPN / Reference	3KL5030-1AG01
Catalog number	50301
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-1AC2DD4A07
Generated	2026-08-05

Product Overview

Switch disconnecter with fuse in new design lu=63 A, Ue = 690 V, 3-pole for BS88 fuse form A2/A3 basic version without 8UC6 handle and shaft

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > SWITCHES-DISCONNECTORS

Additional Product Information

ETIM: EC000216 - Switch disconnecter

Value Unit

Rated short-time withstand current I_{cw} (EF007050) - kA

Degree of protection (NEMA) (EF011959) -

Version as reversing switch (EF009408) -

Switching power at 400 V (EF009166) - kW

Number of switches (EF005586) -

Rated permanent current at AC-21, 400 V (EF009165) - A

Rated operating voltage (EF001435) - V

Colour control element (EF007167) -

Version as main switch (EF006981) true

Version as maintenance-/service switch (EF006986) true

Version as safety switch (EF006985) true

Version as emergency stop installation (EF006959) true

Max. rated operation voltage Ue AC (EF007355) 690 V
Rated permanent current Iu (EF001389) 63.0 A
Rated permanent current at AC-23, 400 V (EF011777) 63 A
Rated operation power at AC-23, 400 V (EF007027) 30.0 kW
Number of poles (EF001391) 3
Number of auxiliary contacts as normally closed contact (EF001377) 0
Number of auxiliary contacts as normally open contact (EF001376) 0
Number of auxiliary contacts as change-over contact (EF003531) 0
Motor drive optional (EF007386) false
Motor drive integrated (EF006697) false
Voltage release optional (EF007491) false
Device construction (EF008240) Built-in device fixed built-in technique
Suitable for floor mounting (EF007243) FALSE
Suitable for front mounting 4-hole (EF007247) false
Suitable for front mounting centre (EF007248) false
Suitable for distribution board installation (EF007262) false
Suitable for intermediate mounting (EF007264) false
Type of control element (E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3KL5030-1AG01 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.