

**INDUSTRIAL COMPONENT DATA**

# 3KL5330-1GJ01 SIEMENS Switch disconnecter with fuse in new design Iu 160 A, Ue 690 V, 3-pole for BS88 fuse f..

Brand: SIEMENS | Manufacturer Part Number: 3KL5330-1GJ01



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | SIEMENS             |
| MPN / Reference | 3KL5330-1GJ01       |
| Catalog number  | 53301               |
| Category        | Switch disconnecter |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-84DE900B20       |
| Generated       | 2026-08-04          |

## Product Overview

Switch disconnecter with fuse in new design Iu=160 A, Ue = 690 V, 3-pole for BS88 fuse form A4 with door operating mechanism 8UC7 Handle dark blue/blue-green Basic masking frame light gray

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > SWITCHES-DISCONNECTORS**

## Additional Product Information

ETIM: EC000216 - Switch disconnector  
Value Unit  
Number of switches (EF005586) -  
Rated operating voltage (EF001435) - V  
Switching power at 400 V (EF009166) - kW  
Colour control element (EF007167) -  
Version as reversing switch (EF009408) -  
Rated permanent current at AC-21, 400 V (EF009165) - A  
Degree of protection (NEMA) (EF011959) -  
Rated short-time withstand current Icw (EF007050) - kA  
Version as main switch (EF006981) true  
Version as maintenance-/service switch (EF006986) true  
Version as safety switch (EF006985) true  
Version as emergency stop installation (EF006959) false

Max. rated operation voltage Ue AC (EF007355) 690 V  
Rated permanent current Iu (EF001389) 160.0 A  
Rated permanent current at AC-23, 400 V (EF011777) 160 A  
Rated operation power at AC-23, 400 V (EF007027) 80.0 kW  
Number of poles (EF001391) 3  
Number of auxiliary contacts as normally closed contact (EF001377) 0  
Number of auxiliary contacts as normally open contact (EF001376) 0  
Number of auxiliary contacts as change-over contact (EF003531) 0  
Motor drive optional (EF007386) false  
Motor drive integrated (EF006697) false  
Voltage release optional (EF007491) false  
Device construction (EF008240) Built-in device fixed built-in technique  
Suitable for floor mounting (EF007243) FALSE  
Suitable for front mounting 4-hole (EF007247) false  
Suitable for front mounting centre (EF007248) false  
Suitable for distribution board installation (EF007262) false  
Suitable for intermediate mounting (EF007264) false  
Type of control element...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3KL5330-1GJ01 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.