

INDUSTRIAL COMPONENT DATA

3KX3521-0AA SIEMENS Accessory for switch 3KL/3KM for rated current up to 63 A Kit for BS fuses

Brand: SIEMENS | Manufacturer Part Number: 3KX3521-0AA



Manufacturer	SIEMENS
MPN / Reference	3KX3521-0AA
Catalog number	35210
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-26D51E2EC1
Generated	2026-08-02

Product Overview

Accessory for switch 3KL/3KM for rated current up to 63 A Kit for BS fuses

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > SWITCHES-DISCONNECTORS**

Additional Product Information

ETIM: EC000216 - Switch disconnecter

Value Unit

Rated operation power at AC-3, 400 V (EF001364) - kW

Switching power at 400 V (EF009166) - kW

Motor drive integrated (EF006697) -

Suitable for front mounting centre (EF007248) -

Number of switches (EF005586) -

Type of electrical connection of main circuit (EF006819) -

Suitable for distribution board installation (EF007262) -

Device construction (EF008240) -

Version as reversing switch (EF009408) -

Degree of protection (NEMA) (EF011959) -

Rated operating voltage (EF001435) - V

Type of control element (EF006976) -

Rated operation power at AC-23, 400 V (EF007027) - kW

Rated short-time withstand current I_{cw} (EF007050) - kA
Colour control element (EF007167) -
Suitable for floor mounting (EF007243) -
Suitable for intermediate mounting (EF007264) -
Rated permanent current I_u (EF001389) - A
Interlockable (EF006281) -
Version as emergency stop installation (EF006959) -
Voltage release optional (EF007491) -
Number of auxiliary contacts as normally closed contact (EF001377) -
Number of poles (EF001391) -
Max. rated operation voltage U_e AC (EF007355) - V
Motor drive optional (EF007386) -
Version as main switch (EF006981) -
Suitable for front mounting 4-hole (EF007247) -
Number of auxiliary contacts as normally open contact (EF001376) -
Number of auxiliary contacts as change-over contact (EF003531) -
Rated permanent current at AC-21, 400 V (EF009165) - A
Conditioned rated short-circuit current I_q (EF001444) - kA
Version as safety switch (EF...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3KX3521-0AA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.