


INDUSTRIAL COMPONENT DATA

3LD2103-2TB53 SIEMENS SENTRON, Switch disconnecter 3LD, emergency switching-off switch, 3- pole, Iu: 25 A, o..

Brand: SIEMENS | Manufacturer Part Number: 3LD2103-2TB53



Manufacturer	SIEMENS
MPN / Reference	3LD2103-2TB53
Catalog number	21032
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-7053A2BE62
Generated	2026-08-02

Product Overview

SETRON, Switch disconnecter 3LD, emergency switching-off switch, 3- pole, Iu: 25 A, operating power / at AC-23 A 400 V: 9.5 kW, front-mounted, rotary operating mechanism, Red / yellow, 4-hole mounting of the handle
 INTERR. PPAL. AND EMERGENCY. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > SWITCHES-DISCONNECTORS**

Additional Product Information

Technical data

SETRON, Switch disconnecter 3LD, emergency switching-off switch, 3- pole, Iu: 25 A, operating power / at AC-23 A 400 V: 9.5 kW, front-mounted, rotary operating mechanism, Red / yellow, 4-hole mounting of the handle

Model

product brand name SETRON

product designation 3LD Switch disconnecter

design of the product EMERGENCY-STOP switch

display version / for switch position indicator manual operation 1 ON - 0 OFF

design of the actuating element Short rotary knob

design of handle rotary operating mechanism, red/yellow

type of the driving mechanism / motor drive No

General technical data

number of poles 3

type of device fixed mounting

type of switch front mounted

size of switch disconnecter 2

mechanical service life (switching cycles) / typical 100 000

electrical endurance (switching cycles)

? at AC-23 A / at 690 V 6 000

I²t value / with closed switch / at 690 V / for combination switch + gG fuse / maximum 4 kA².s

let-through I²t value / with closed switch / at 440 V / for combination switch + gG fuse / maximum 4 kA².s

operating frequency / maximum 50 1/h

Voltage

insulation voltage / rated value 690 V

surge voltage resistance / rated value 6 kV

Protection class

protection class IP IP65

degree of protection NEMA rating 1, 3R, 4X, 12

protection class IP / on the front IP65

Dissipation

power loss [W]

? for rated value of the current / at AC / in hot operating state / per pole 1.1 W

? per conductor / typical 1 W

Current

operational current

? at 40 °C / rated value 25....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3LD2103-2TB53 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.