

INDUSTRIAL COMPONENT DATA

3LD2115-0TK53-0AB0 SIEMENS SENTRON, Switch disconnecter 3LD, emergency switching-off switch, 3- pole, lu: 25..

Brand: SIEMENS | Manufacturer Part Number: 3LD2115-0TK53-0AB0



Manufacturer	SIEMENS
MPN / Reference	3LD2115-0TK53-0AB0
Catalog number	21150
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-9FC30F6757
Generated	2026-08-04

Product Overview

SENTRON, Switch disconnecter 3LD, emergency switching-off switch, 3- pole, lu: 25 A, operating power / at AC-23 A 400 V: 9.5 kW, floor mounting with door coupling, rotary operating mechanism, Red / yellow, 4-hole mounting of the handle, without tolerance compensation, Installation dimension 190mm

INTERR.PPAL./PAR. EMERG. 3 poles IU=25, P/AC-23A WITH 400V=9,5KW FIXATION BASED FIXATION PROFILE/2 HOLES MYO ROTATING DOOR RED DOOR / WITHOUT COMP. TOLERANCE DIM. MOUNT 190MM. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > SWITCHES-DISCONNECTORS

Additional Product Information

Technical data

SENTRON, Switch disconnecter 3LD, emergency switching-off switch, 3- pole, lu: 25 A, operating power / at AC-23 A 400 V: 9.5 kW, floor mounting with door coupling, rotary operating mechanism, Red / yellow, 4-hole mounting of the handle, without tolerance compensation, Installation dimension 190mm

Model

product brand name SENTRON

product designation 3LD Switch disconnecter

design of the product EMERGENCY-STOP switch

display version / for switch position indicator manual operation 1 ON - 0 OFF
design of the actuating element Short rotary knob
design of handle rotary operating mechanism, red/yellow
type of the driving mechanism / motor drive No
General technical data
number of poles 3
type of device fixed mounting
type of switch Floor mounting with door coupling
size of switch disconnecter 2
mechanical service life (switching cycles) / typical 100 000
electrical endurance (switching cycles)
? at AC-23 A / at 690 V 6 000
I_{2t} value / with closed switch / at 690 V / for combination switch + gG fuse / maximum 4 kA_{2.s}
let-through I_{2t} value / with closed switch / at 440 V / for combination switch + gG fuse / maximum 4 kA_{2.s}
operating frequency / maximum 50 1/h
Voltage
insulation voltage / rated value 690 V
surge voltage resistance / rated value 6 kV
Protection class
protection class IP IP65
degree of protection NEMA rating 1, 3R, 4X, 12
protection class IP / on the front IP65
Dissipation
power loss [W]
? for rated value of the current / at AC / in hot operating state /...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3LD2115-0TK53-0AB0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.