

## INDUSTRIAL COMPONENT DATA

# 3LD2122-0TK11-0AE1 SIEMENS SENTRON, Switch disconnecter 3LD, main switch, 3-pole, Iu: 25 A, Operating power ..

Brand: SIEMENS | Manufacturer Part Number: 3LD2122-0TK11-0AE1



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | SIEMENS             |
| MPN / Reference | 3LD2122-0TK11-0AE1  |
| Catalog number  | 21220               |
| Category        | Switch disconnecter |
| Minimum order   | 8 Pcs               |
| Document ID     | EO-9A2110918F       |
| Generated       | 2026-08-04          |

## Product Overview

SENTRON, Switch disconnecter 3LD, main switch, 3-pole, Iu: 25 A, Operating power / at AC-23 A at 400 V: 9.5 kW, floor mounting with door coupling, knob-operated mechanism, black, 4-hole mounting of the handle, non can be locked  
INTERR. MAIN 3 POLES IU=25, P/AC-23A WITH 400V=9,5KW FIXED FRONT FIXATION FOUR DRILLS \*\*\* SPECIAL VERSION \*\*\* MULETILLA NETAMA, NON-LOCKABLE ( \*\* ATTENTION : Price per 1 Unit and Minimum Quantity / Multiplo of Order 8 Units \*\* )

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path

SIEMENS &gt; POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR &gt; SWITCHES-DISCONNECTORS

## Additional Product Information

## Technical data

SENTRON, Switch disconnecter 3LD, main switch, 3-pole, Iu: 25 A, Operating power / at AC-23 A at 400 V: 9.5 kW, floor mounting with door coupling, knob-operated mechanism, black, 4-hole mounting of the handle, non can be locked

Model

product brand name SENTRON

product designation 3LD Switch disconnecter

design of the product Main switch

display version / for switch position indicator manual operation 1 ON - 0 OFF

design of the actuating element selector switch

design of handle knob-operated mechanism, black

type of the driving mechanism / motor drive No

General technical data

number of poles 3

type of device fixed mounting

type of switch Floor mounting with door coupling

size of switch disconnecter 2

mechanical service life (switching cycles) / typical 100 000

electrical endurance (switching cycles)

? at AC-23 A / at 690 V 6 000

I<sub>2t</sub> value / with closed switch / at 690 V / for combination switch + gG fuse / maximum 4 kA<sup>2</sup>.s

let-through I<sub>2t</sub> value / with closed switch / at 440 V / for combination switch + gG fuse / maximum 4 kA<sup>2</sup>.s

operating frequency / maximum 50 1/h

Voltage

insulation voltage / rated value 690 V

surge voltage resistance / rated value 6 kV

Protection class

protection class IP IP65

degree of protection NEMA rating 1, 3R, 4X, 12

protection class IP / on the front IP65

Dissipation

power loss [W]

? for rated value of the current / at AC / in hot operating state / per pole 1.1 W

? per conductor / typical 1 W

Current

operational current

? at 40 °C / rat...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3LD2122-0TK11-0AE1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.