

INDUSTRIAL COMPONENT DATA

3LD2230-2EQ13-0AC1 SIEMENS SENTRON, Switch disconnecter 3LD, emergency switching-off switch, 4- pole, Iu: 32..

Brand: SIEMENS | Manufacturer Part Number: 3LD2230-2EQ13-0AC1



Manufacturer	SIEMENS
MPN / Reference	3LD2230-2EQ13-0AC1
Catalog number	22302
Category	Switch disconnecter
Minimum order	20 Pcs
Document ID	EO-63108A11A7
Generated	2026-08-04

Product Overview

SENTRON, Switch disconnecter 3LD, emergency switching-off switch, 4- pole, Iu: 32 A, operating power / at AC-23 A 400 V: 11.5 kW, installation in distribution boards, 1 NC, 1 NO, knob-operated mechanism, Red / yellow, handle direct at the switch

INTERR. PPAL/PAR. EMERG. 3POLOS IU=32, P/AC-23A WITH 400V=11,5KW RED/YELLOW CRUTCH *** SPECIAL VERSION *** (** ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiplication 20 Units **). Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > SWITCHES-DISCONNECTORS

Additional Product Information

Technical data

SENTRON, Switch disconnecter 3LD, emergency switching-off switch, 4- pole, Iu: 32 A, operating power / at AC-23 A 400 V: 11.5 kW, installation in distribution boards, 1 NC, 1 NO, knob-operated mechanism, Red / yellow, handle direct at the switch

Model

product brand name SENTRON

product designation 3LD Switch disconnecter

design of the product EMERGENCY-STOP switch

display version / for switch position indicator manual operation 1 ON - 0 OFF

design of the actuating element selector switch

design of handle knob-operated mechanism, red/yellow

type of the driving mechanism / motor drive No

General technical data

number of poles 4

type of device fixed mounting

type of switch DIN-rail mounting

size of switch disconnecter 2

mechanical service life (switching cycles) / typical 100 000

electrical endurance (switching cycles)

? at AC-23 A / at 690 V 6 000

I_{2t} value / with closed switch / at 690 V / for combination switch + gG fuse / maximum 9 kA².s

let-through I_{2t} value / with closed switch / at 440 V / for combination switch + gG fuse / maximum 9 kA².s

operating frequency / maximum 50 1/h

Voltage

insulation voltage / rated value 690 V

surge voltage resistance / rated value 6 kV

Protection class

protection class IP IP40

protection class IP / on the front IP40

Dissipation

power loss [W]

? for rated value of the current / at AC / in hot operating state / per pole 1.8 W

? per conductor / typical 2 W

Current

operational current

? at 40 °C / rated value 32 A

? at 45 °C / rat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3LD2230-2EQ13-0AC1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.