

INDUSTRIAL COMPONENT DATA

3LD2248-0TK51 SIEMENS SENTRON, Switch disconnecter 3LD, main switch, 3-pole, Iu: 32 A, Operating power / at ..

Brand: SIEMENS | Manufacturer Part Number: 3LD2248-0TK51



Manufacturer	SIEMENS
MPN / Reference	3LD2248-0TK51
Catalog number	22480
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-B9895D040E
Generated	2026-08-01

Product Overview

SENTRON, Switch disconnecter 3LD, main switch, 3-pole, Iu: 32 A, Operating power / at AC-23 A at 400 V: 11.5 kW, floor mounting with door coupling, rotary operating mechanism, black, central mounting 22.5 mm of the handle, without tolerance compensation

INTERR.PPAL./PAR. EMERG. 3 poles IU=32, P/AC-23A WITH 400V=11,5KW FIXATION BASED FIXATION PROFILE/2 HOLES MYO ROTATING DOOR NETAMO FIXING CENTRAL DRILL. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > SWITCHES-DISCONNECTORS**

Additional Product Information

Technical data

SENTRON, Switch disconnecter 3LD, main switch, 3-pole, Iu: 32 A, Operating power / at AC-23 A at 400 V: 11.5 kW, floor mounting with door coupling, rotary operating mechanism, black, central mounting 22.5 mm of the handle, without tolerance compensation

Model

product brand name SENTRON

product designation 3LD Switch disconnecter

design of the product Main switch

display version / for switch position indicator manual operation 1 ON - 0 OFF

design of the actuating element Short rotary knob

design of handle rotary operating mechanism, black

type of the driving mechanism / motor drive No

General technical data

number of poles 3

type of device fixed mounting

type of switch Floor mounting with door coupling

size of switch disconnecter 2

mechanical service life (switching cycles) / typical 100 000

electrical endurance (switching cycles)

? at AC-23 A / at 690 V 6 000

I2t value / with closed switch / at 690 V / for combination switch + gG fuse / maximum 9 kA2.s

Iet-through I2t value / with closed switch / at 440 V / for combination switch + gG fuse / maximum 9 kA2.s

operating frequency / maximum 50 1/h

Voltage

insulation voltage / rated value 690 V

surge voltage resistance / rated value 6 kV

Protection class

protection class IP IP65

degree of protection NEMA rating 1, 3R, 4X, 12

protection class IP / on the front IP65

Dissipation

power loss [W]

? for rated value of the current / at AC / in hot operating state / per pole 1.8 W

? per conductor / typical 2 W

Current

opera...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3LD2248-0TK51 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.