

INDUSTRIAL COMPONENT DATA

3LD2265-7UL01-0AD8 SIEMENS SENTRON, Switch disconnecter 3LD, change-over switch, 4-pole, Iu: 32 A, Operating..

Brand: SIEMENS | Manufacturer Part Number: 3LD2265-7UL01-0AD8



Manufacturer	SIEMENS
MPN / Reference	3LD2265-7UL01-0AD8
Catalog number	22657
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-5DD1458EEF
Generated	2026-08-03

Product Overview

SENTRON, Switch disconnecter 3LD, change-over switch, 4-pole, Iu: 32 A, Operating power / at AC-23 A at 400 V: 11.5 kW, molded-plastic encapsulation for metric cable screw connection, knob-operated mechanism, black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > SWITCHES-DISCONNECTORS**

Additional Product Information

Technical data

SENTRON, Switch disconnecter 3LD, change-over switch, 4-pole, Iu: 32 A, Operating power / at AC-23 A at 400 V: 11.5 kW, molded-plastic encapsulation for metric cable screw connection, knob-operated mechanism, black

Model

product brand name SENTRON

product designation 3LD Switch disconnecter

design of the product Selector switch

display version / for switch position indicator manual operation 1 ON - 0 OFF - 2 ON

design of the actuating element selector switch

design of handle knob-operated mechanism, black

type of the driving mechanism / motor drive No

General technical data

number of poles 4
type of device fixed mounting
type of switch Molded-plastic enclosure for metric threaded joint
size of switch disconnecter 2
mechanical service life (switching cycles) / typical 100 000
electrical endurance (switching cycles)
? at AC-23 A / at 690 V 6 000
I_{2t} value / with closed switch / at 690 V / for combination switch + gG fuse / maximum 9 kA_{2s}
let-through I_{2t} value / with closed switch / at 440 V / for combination switch + gG fuse / maximum 9 kA_{2s}
operating frequency / maximum 50 1/h
Voltage
insulation voltage / rated value 690 V
surge voltage resistance / rated value 6 kV
Protection class
protection class IP IP65
degree of protection NEMA rating 1, 4X, 12
protection class IP / on the front IP65
Dissipation
power loss [W]
? for rated value of the current / at AC / in hot operating state / per pole 1.8 W
? per conductor / typical 2 W
Current
operational current
? at...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3LD2265-7UL01-0AD8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.