

INDUSTRIAL COMPONENT DATA

3LD2405-1TL13 SIEMENS SENTRON, Switch disconnecter 3LD, emergency switching-off switch, 4- pole, Iu 250 A, o..

Brand: SIEMENS | Manufacturer Part Number: 3LD2405-1TL13



Manufacturer	SIEMENS
MPN / Reference	3LD2405-1TL13
Catalog number	24051
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-4A7CD1BD82
Generated	2026-08-03

Product Overview

SENTRON, Switch disconnecter 3LD, emergency switching-off switch, 4- pole, Iu=250 A, operating power / at AC-23 A 400 V: 132 kW, front-mounted, knob-operated mechanism, red/yellow, 4-hole mounting of the handle
4-POLE MAIN SWITCH FIXING ON THE BASE IU=250A,P/AC-23A AT 400V=132KW ACTUATE. TURN. RED/LOVE..

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > SWITCHES-DISCONNECTORS

Additional Product Information

Technical data

SENTRON, Switch disconnecter 3LD, emergency switching-off switch, 4- pole, Iu=250 A, operating power / at AC-23 A 400 V: 132 kW, front-mounted, knob-operated mechanism, red/yellow, 4-hole mounting of the handle

Model

product brand name SENTRON

product designation 3LD Switch disconnecter

design of the product EMERGENCY-STOP switch

display version / for switch position indicator manual operation 1 ON - 0 OFF

design of the actuating element selector switch

design of handle knob-operated mechanism, red/yellow

type of the driving mechanism / motor drive No

General technical data

number of poles 4

type of device fixed mounting
type of switch front mounted
size of switch disconnecter 5
mechanical service life (switching cycles) / typical 100 000
electrical endurance (switching cycles)
? at AC-23 A / at 690 V 6 000
I²t value / with closed switch / at 690 V / for combination switch + gG fuse / maximum 557 kA².s
let-through I²t value / with closed switch / at 440 V / for combination switch + gG fuse / maximum 557 kA².s
operating frequency / maximum 50 1/h
Voltage
insulation voltage / rated value 690 V
surge voltage resistance / rated value 8 kV
Protection class
protection class IP IP65
degree of protection NEMA rating 1, 3R, 4X, 12
protection class IP / on the front IP65
Dissipation
power loss [W]
? for rated value of the current / at AC / in hot operating state / per pole 36 W
? per conductor / typical 36 W
Current
operational current
? at 40 °C / rated value 250 A
? a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3LD2405-1TL13 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.