

INDUSTRIAL COMPONENT DATA

3LD3254-0TL53 SIEMENS Load disconnecter 3LD3, lu 32 A Main switch 3-pole + N Rated operating capacity for AC..

Brand: SIEMENS | Manufacturer Part Number: 3LD3254-0TL53



Manufacturer	SIEMENS
MPN / Reference	3LD3254-0TL53
Catalog number	32540
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-DF3A3EC308
Generated	2026-08-03

Product Overview

Load disconnecter 3LD3, lu 32 A Main switch 3-pole + N Rated operating capacity for AC-23 A at 400V 11.5kW Front plate mounting Basic switch with Central hole mounting 22.5mm Rotary actuator red / yellow 66 x 66 mm
INTERR. PPAL 3LD3 3 POLOS + N, LU 32A P/AC WITH 400V = 11.5 kW FRONT FIXING FIXING IN SINGLE DRILL 22.5 MM WITH RED/YELLOW ROTARY DRIVE 66 x66 mm. Cancellations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > SWITCHES-DISCONNECTORS

Additional Product Information

Technical data

Load disconnecter 3LD3, lu 32 A Main switch 3-pole + N Rated operating capacity for AC-23 A at 400V 11.5kW Front plate mounting Basic switch with Central hole mounting 22.5mm Rotary actuator red / yellow 66 x 66 mm

Model

product brand name SENTRON

product designation 3LD Switch disconnecter

design of the product EMERGENCY-STOP switch

display version / for switch position indicator manual operation 1 ON - 0 OFF

design of the actuating element Short rotary knob

design of handle rotary operating mechanism, red/yellow

type of the driving mechanism / motor drive No

General technical data

number of poles 4
number of poles / note 4
type of device fixed mounting
type of switch front mounted
mechanical service life (switching cycles) / typical 100 000
electrical endurance (switching cycles)
? at AC-23 A / at 690 V 6 000
I2t value / with closed switch / at 690 V / for combination switch + gG fuse / maximum 9 kA2.s
let-through I2t value / with closed switch / at 440 V / for combination switch + gG fuse / maximum 9 kA2.s
operating frequency / maximum 50 1/h
Voltage
insulation voltage / rated value 690 V
surge voltage resistance / rated value 6 kV
Protection class
protection class IP IP65
degree of protection NEMA rating 1, 3R, 4X, 12
protection class IP / on the front IP65
Dissipation
power loss [W]
? for rated value of the current / at AC / in hot operating state / per pole 1.8 W
? per conductor / typical 2 W
Current
operational current
? at 40 °C / rated value 32 A
? at...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3LD3254-0TL53 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.