

INDUSTRIAL COMPONENT DATA

3NA6244-6 SIEMENS LV HRC fuse element, NH2, In: 250 A, gG, Un AC: 690 V, Un DC: 440 V, Combined indicator, I..

Brand: SIEMENS | Manufacturer Part Number: 3NA6244-6



Manufacturer	SIEMENS
MPN / Reference	3NA6244-6
Catalog number	62446
Category	Low Voltage HRC fuse
Minimum order	3 Pcs
Document ID	EO-A80727D53B
Generated	2026-08-06

Product Overview

LV HRC fuse element, NH2, In: 250 A, gG, Un AC: 690 V, Un DC: 440 V, Combined indicator, Insulated grip lugs
NH gL/gG fuse cartridge with voltage-free lug with central indicator tam.2, 250A, AC 690V/DC 440V (** ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 3 Units **). Cancelations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > NH fuses
--------------	--

Additional Product Information

Technical data

LV HRC fuse element, NH2, In: 250 A, gG, Un AC: 690 V, Un DC: 440 V, Combined indicator, Insulated grip lugs

Model

product brand name SENTRON

product designation LV HRC fuse link

design of the product With blade contacts

design of an identification indicator Combination alarms

design of the switching contact Non-corroding, silver-plated

design of the fuse link LV HRC fuse link

General technical data

size of fuse system / according to EN 60269-1 NH2

operating class of the fuse link gG

mounting type insulated grip lugs

type of voltage / of the operating voltage AC/DC

supply voltage

? at AC / rated value 690 V

? at DC 440 V

Protection class

protection class IP IP20, with connected conductors

Switching capacity

switching capacity current

? at DC / according to IEC 60947-2 / rated value 25 kA

? according to IEC 60947-2 / rated value 120 kA

Dissipation

power loss [W] 23 W

power loss [W] / for rated value of the current / at AC / in hot operating state / per pole 23 W

Current

operational current

? at 30 °C / rated value 245 A

? at 40 °C / rated value 237.5 A

? at 45 °C / rated value 230 A

? at 50 °C / rated value 225 A

? at 55 °C / rated value 220 A

? at 60 °C / rated value 215 A

? at AC / rated value 250 A

Mechanical Design

width / of the enclosure 57.8 mm

mounting position Any, preferably vertical

net weight 647 g

Environmental conditions

ambient temperature / during operation

? minimum -5 °C

? maximum 40 °C

environmental category -20 to +50 at 95% relative humidit...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3NA6244-6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.