

INDUSTRIAL COMPONENT DATA

3NC5531 SIEMENS SITOR fuse link, with internal thread and bolt terminal, In: 350 A, aR, Un AC: 800 V, Un DC:..

Brand: SIEMENS | Manufacturer Part Number: 3NC5531



Manufacturer	SIEMENS
MPN / Reference	3NC5531
Catalog number	10000
Category	Low Voltage HRC fuse
Minimum order	3 Pcs
Document ID	EO-1BC368740C
Generated	2026-08-05

Product Overview

SITOR fuse link, with internal thread and bolt terminal, In: 350 A, aR, Un AC: 800 V, Un DC: 440 V, front indicator

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > SITOR Extra-fast Fuses

Additional Product Information

ETIM: EC000055 - Low Voltage HRC fuse

Value Unit

Insulated metal gripping lugs (IMGL) (EF012538) -

Voltage type (EF000187) -

Construction size (EF002566) Other

Rated current (EF000227) 350 A

Rated voltage (EF000228) 800 V

Rated switching capacity (EF002563) 100.0 kA

Utilization category (EF002572) aR (accompanied semiconductor protection)

Type of fuse status indicator (EF004473) Top fuse status indicator

SITOR fuse link, with internal thread and bolt terminal, In: 350 A, aR, Un AC: 800 V, Un DC: 440 V, front indicator

Model

product brand name SENTRON

Product designation SITOR fuse link

Design of the product With female thread and stud terminal

Design of an identification indicator front indicator
Design of the fuse link Fuses for special applications
General technical data
Size of fuse system / acc. to DIN EN 60269-1 others
Operating class of the fuse link aR
Varying load factor (WL) 0.9
Supply voltage
type of voltage AC/DC
Operating current / at AC / rated value 350 A
Supply voltage
? at AC / rated value 800 V
? at DC 440 V
Switching capacity
Switching capacity current
? acc. to IEC 60947-2 / rated value 100 kA
Dissipation
Power loss [W] 80 W
? Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole 80 W
? power loss [W] / maximum 80 W
Product details
product description Not non-interchangeable
Mechanical Design
mounting position Any, preferably vertical
net weight 632 g
Environmental conditions
Ambient temperature
? minimum -20 °C
? maxi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3NC5531 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.