

INDUSTRIAL COMPONENT DATA

3NE3333 SIEMENS SITOR fuse link, with slotted blade contacts, NH2, In: 450 A, aR, Un AC: 1000 V, front indic..

Brand: SIEMENS | Manufacturer Part Number: 3NE3333



Manufacturer	SIEMENS
MPN / Reference	3NE3333
Catalog number	10000
Category	Low Voltage HRC fuse
Minimum order	3 Pcs
Document ID	EO-6D75F57FC7
Generated	2026-08-05

Product Overview

SITOR fuse link, with slotted blade contacts, NH2, In: 450 A, aR, Un AC: 1000 V, front indicator

Fuse SITOR 450A, AC 1000V, GR.2/110mm (** ATTENTION : Price per 1 Unit and Minimum Quantity / Order Multiple 3 Units **). Cancellations and returns limited. Consult conditions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > SITOR Extra-fast Fuses**

Additional Product Information

Technical data

SITOR fuse link, with slotted blade contacts, NH2, In: 450 A, aR, Un AC: 1000 V, front indicator

Model

product brand name SENTRON

product designation SITOR fuse link

design of the product With slotted blade contacts

design of an identification indicator front indicator

design of the switching contact With blade contacts, silver-plated

design of the fuse link SITOR, LV HRC design

General technical data

size of fuse system / according to EN 60269-1 NH2

operating class of the fuse link aR

varying load factor (WL) 1

type of voltage / of the operating voltage AC

Supply voltage

supply voltage

? at AC / rated value 1 000 V

Switching capacity

switching capacity current

? according to IEC 60947-2 / rated value 100 kA

Dissipation

power loss [W] 90 W

power loss [W]

? for rated value of the current / at AC / in hot operating state / per pole 90 W

? maximum 90 W

Current

operational current

? at 30 °C / rated value 450 A

? at 40 °C / rated value 450 A

? at 45 °C / rated value 450 A

? at 50 °C / rated value 445.5 A

? at 55 °C / rated value 441 A

? at 60 °C / rated value 436.5 A

? at AC / rated value 450 A

Product details

product description Not non-interchangeable

Mechanical Design

mounting position Any, preferably vertical

Environmental conditions

ambient temperature / during operation

? minimum -20 °C

? maximum 50 °C

environmental category -20 to +50 at 95% relative humidity

Downloads and manuals

General Product Approval Declaration of Conformity

Confirmation

UK Declaratio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3NE3333 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.