

INDUSTRIAL COMPONENT DATA

3NE5336-0MK66 SIEMENS SITOR fuse link, with slotted blade contacts, NH2, In: 630 A, aR, Un AC: 1500 V, Un DC..

Brand: SIEMENS | Manufacturer Part Number: 3NE5336-0MK66



Manufacturer	SIEMENS
MPN / Reference	3NE5336-0MK66
Catalog number	53360
Category	Low Voltage HRC fuse
Minimum order	1 Pcs
Document ID	EO-6C200CDD77
Generated	2026-08-06

Product Overview

SITOR fuse link, with slotted blade contacts, NH2, In: 630 A, aR, Un AC: 1500 V, Un DC: 1000 V, without Indicator PROTEC FUSE. SEMICOND. SITOR 630A AR 1500V AC/1100V DC. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > SITOR Extra-fast Fuses

Additional Product Information

Technical data

SITOR fuse link, with slotted blade contacts, NH2, In: 630 A, aR, Un AC: 1500 V, Un DC: 1000 V, without Indicator Model

product brand name SENTRON

product designation SITOR fuse link

design of the product With slotted blade contacts

design of an identification indicator Without indicator

design of the switching contact With bolt-on links, silver-plated

design of the fuse link SITOR, LV HRC design

General technical data

size of fuse system / according to EN 60269-1 NH2

operating class of the fuse link aR

type of voltage / of the operating voltage AC/DC

Supply voltage

supply voltage

? at AC / rated value 1 500 V

? at DC 1 000 V

Dissipation

power loss [W] 85 W

power loss [W]

? for rated value of the current / at AC / in hot operating state / per pole 85 W

Current

operational current

? at 30 °C / rated value 630 A

? at 40 °C / rated value 630 A

? at 45 °C / rated value 630 A

? at 50 °C / rated value 623.7 A

? at 55 °C / rated value 611.23 A

? at 60 °C / rated value 592.89 A

? at AC / rated value 630 A

Product details

product description Not non-interchangeable

Mechanical Design

mounting position Any, preferably vertical

net weight 1 316 g

Environmental conditions

ambient temperature / during operation

? minimum -20 °C

? maximum 50 °C

environmental category -20 to +50 at 95% relative humidity

Downloads and manuals

General Product Approval Declaration of Conformity other

Confirmation

UK Declaration of Conformity

Miscellaneous

Further information

Information- and Dow...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3NE5336-0MK66 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.