

## INDUSTRIAL COMPONENT DATA

# 3NH3330 SIEMENS LV HRC fuse base Sz. 2, 1-pole 400 A 690 V (1000 V) flat terminal

Brand: SIEMENS | Manufacturer Part Number: 3NH3330



|                 |                           |
|-----------------|---------------------------|
| Manufacturer    | SIEMENS                   |
| MPN / Reference | 3NH3330                   |
| Catalog number  | 10000                     |
| Category        | Low Voltage HRC fuse base |
| Minimum order   | 1 Pcs                     |
| Document ID     | EO-3DDA5E4EC6             |
| Generated       | 2026-08-03                |

## Product Overview

LV HRC fuse base Sz. 2, 1-pole 400 A 690 V (1000 V) flat terminal

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path SIEMENS &gt; POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR &gt; NH fuses

## Additional Product Information

## Technical data

LV HRC fuse base Sz. 2, 1-pole 400 A 690 V (1000 V) flat terminal

## Model

product brand name SENTRON

product designation LV HRC fuse system

design of the thread / of the connection screw M10

design of the product LV HRC fuse base

## General technical data

number of poles 1

size of fuse system / according to EN 60269-1 NH2

utilization category Without

Supply voltage

supply voltage

? at AC / rated value 690 V

? at DC 440 V

**Current**

operational current

? at 35 °C / rated value 376 A

? at 40 °C / rated value 368 A

? at 45 °C / rated value 356.16 A

? at 50 °C / rated value 344 A

? at 55 °C / rated value 332.16 A

? at 60 °C / rated value 324.16 A

? at 65 °C / rated value 308.16 A

? at 70 °C / rated value 296 A

? at AC / rated value 400 A

**Product details**

product component / swivel-in mechanism No

breaking capacity maximum short-circuit current (Icu)

? at AC / rated value 120 kA

? at DC / rated value 25 kA

**Connections**

tightening torque / with screw-type terminals / maximum 38 N·m

type of electrical connection With flat-type terminal

? for main current circuit flat connector

**Mechanical Design**

height 227 mm

width 49 mm

depth 90 mm

fastening method fixed mounting

fastening method / bus-mounting No

net weight 817 g

**Downloads and manuals**

General Product Approval Declaration of Conformity

Confirmation

UK Declaration of Conformity

Test Certificates Marine / Shipping other

Special Test Certificate

Type Test Certificates/Test Report

Environmental Confirmations

Miscellaneous

Miscella...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3NH3330 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.