

INDUSTRIAL COMPONENT DATA

3NH7330 SIEMENS LV HRC fuse base Sz. 3630 A (Sz. 2400 A) 690 V 1-pole with swivel equipment with flat termin..

Brand: SIEMENS | Manufacturer Part Number: 3NH7330



Manufacturer	SIEMENS
MPN / Reference	3NH7330
Catalog number	10000
Category	Low Voltage HRC fuse base
Minimum order	1 Pcs
Document ID	EO-7015A89F54
Generated	2026-08-05

Product Overview

LV HRC fuse base Sz. 3630 A (Sz. 2400 A) 690 V 1-pole with swivel equipment with flat terminal

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > NH fuses**

Additional Product Information

ETIM: EC000067 - Low Voltage HRC fuse base

Value Unit

Bus-mounting type (EF002573) -

Construction size (EF002566) NH3

Number of poles (EF001391) 1

Rated current (EF000227) 630 A

Swivelling mechanism (EF002574) true

LV HRC fuse base Sz. 3630 A (Sz. 2400 A) 690 V 1-pole with swivel equipment with flat terminal

Model

product brand name SENTRON

Product designation LV HRC fuse system

Design of the thread / of the connection screw M12

Design of the product LV HRC fuse bases with swivel mechanism

General technical data

number of poles 1

Size of fuse system / acc. to DIN EN 60269-1 NH3

circuit-breaker / Design 3NH73

Supply voltage

Operating current / at AC / rated value 630 A

Supply voltage

? at AC / rated value 690 V

? at DC 440 V

Current

Tripping residual / rated value / derated current / at 40 Cel 579.6 A

Product details

Product component / Swivel mechanism Yes

Maximum short-circuit current breaking capacity (Icu)

? at AC / rated value 120 kA

? at DC / rated value 25 kA

Connections

Tightening torque / with screw-type terminals / maximum 38 N·m

? type of electrical connection for mounting on mounting plate

? Type of electrical connection / for main current circuit flat connector

Mechanical Design

Height 285.5 mm

Width 90 mm

Depth 153.5 mm

Mounting type fixed mounting

Mounting type

? bus-mounting No

net weight 2 075 g

Certificates

? reference code / acc. to DIN EN 61346-2 F

? Reference code / acc. to DIN EN 81346-2 F

Declaration of Conformity other

Environmental Confirmations

Furth...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3NH7330 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.