

INDUSTRIAL COMPONENT DATA

3NP1133-1BC13 SIEMENS SENTRON, Fuse switch disconnecter 3NP1, 3-pole, NH00, 160 A, for Busbar system 8US 60 ..

Brand: SIEMENS | Manufacturer Part Number: 3NP1133-1BC13



Manufacturer	SIEMENS
MPN / Reference	3NP1133-1BC13
Catalog number	11331
Category	Fuse switch disconnecter
Minimum order	1 Pcs
Document ID	EO-94330A7754
Generated	2026-08-05

Product Overview

SENTRON, Fuse switch disconnecter 3NP1, 3-pole, NH00, 160 A, for Busbar system 8US 60 mm, flat terminal, Fuse monitoring: electronic EFM20, Cover level 32/70 mm

DISCONNECTOR UNDER LOAD WITH FUSES 3 POLES, NH00, 160A FOR 60MM BUSBAR SYSTEMS WITH ELECTRONIC FUSE CONTROL, EFM 20. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > SWITCHES-DISCONNECTORS

Additional Product Information

Technical data

SENTRON, Fuse switch disconnecter 3NP1, 3-pole, NH00, 160 A, for Busbar system 8US 60 mm, flat terminal, Fuse monitoring: electronic EFM20, Cover level 32/70 mm

Model

product brand name SENTRON

product designation 3NP1 fuse switch disconnecter

design of the product cover level 32/70 mm

busbar design busbar thickness 5 or 10 mm

design of the safety monitoring electronic EFM 20

design of the actuating element Cover handle

design of the load switch / strip form No
type of the driving mechanism / motor drive No
General technical data
number of poles 3
type of device For 60 mm 8US busbar system
size of disconnecting link 00 and 000
size of fuse link NH000, NH00
let-through current / with closed switch / maximum permissible 23 kA
mechanical service life (switching cycles) / typical 2 000
power factor
? at AC-22 B 0.65
? at AC-23 B 0.45
? with capacitive load -0.25
fuse system LV HRC fuse
degree of pollution 2
Voltage
insulation voltage
? rated value 690 V
? with degree of pollution 3 / at AC / rated value 690 V
? with degree of pollution 2 / at AC / rated value 1 000 V
power factor / at AC-21 B 0.95
surge voltage resistance / rated value 8 kV
operating voltage
? at AC / rated value / minimum 230 V
? at AC / rated value / maximum 690 V
Protection class
protection class IP
? with closed switch / with cover or cable lug cover IP40
? with closed switch / without cover or cable lug cover IP30
? open IP20
? on the front IP40
Dissipation
power loss [W]
? with conventional....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3NP1133-1BC13 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.