

INDUSTRIAL COMPONENT DATA

3NP1163-1JC10 SIEMENS SENTRON, Fuse switch disconnecter 3NP1, 3-pole, NH3, 630 A, for Rittal busbar system 6..

Brand: SIEMENS | Manufacturer Part Number: 3NP1163-1JC10



Manufacturer	SIEMENS
MPN / Reference	3NP1163-1JC10
Catalog number	11631
Category	Fuse switch disconnecter
Minimum order	1 Pcs
Document ID	EO-1799A6BB92
Generated	2026-08-05

Product Overview

SENTRON, Fuse switch disconnecter 3NP1, 3-pole, NH3, 630 A, for Rittal busbar system 60 mm, flat terminal, Cover level 32/70 mm

LOAD DISCONNECT WITH 3-POLE FUSES, NH3, 630A FOR 60MM BUSBAR SYSTEMS RITTAL FLAT CONNECTOR COVER.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > SWITCHES-DISCONNECTORS

Additional Product Information

Technical data

SENTRON, Fuse switch disconnecter 3NP1, 3-pole, NH3, 630 A, for Rittal busbar system 60 mm, flat terminal, Cover level 32/70 mm

Model

product brand name SENTRON

product designation 3NP1 fuse switch disconnecter

design of the product cover level 32/70 mm

busbar design busbar thickness 5 or 10 mm

design of the safety monitoring Without

design of the actuating element Cover handle

design of the load switch / strip form No
type of the driving mechanism / motor drive No
General technical data
number of poles 3
type of device For Rittal 60 mm busbar system
size of disconnecting link 3 and 2
size of fuse link NH2, NH3
let-through current / with closed switch / maximum permissible 60 kA
mechanical service life (switching cycles) / typical 1 000
power factor
? at AC-22 B 0.65
? at AC-23 B 0.35
? with capacitive load -0.25
fuse system LV HRC fuse
degree of pollution 3
Voltage
insulation voltage
? rated value 690 V
? with degree of pollution 3 / at AC / rated value 690 V
? with degree of pollution 2 / at AC / rated value 1 000 V
power factor / at AC-21 B 0.95
surge voltage resistance / rated value 8 kV
operating voltage
? at AC / rated value / maximum 690 V
? at DC / rated value 440 V
? at DC / rated value / maximum 440 V
Protection class
protection class IP
? with closed switch / with cover or cable lug cover IP40
? with closed switch / without cover or cable lug cover IP30
? open IP20
? on the front IP40
Dissipation
power loss [W]
? with conventional rated thermal curr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3NP1163-1JC10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.