

INDUSTRIAL COMPONENT DATA

3NP5065-1HF13 SIEMENS SENTRON, Fuse switch disconnecter 3NP5, 3-pole, NH00, 160 A, with Adapter for Busbar s..

Brand: SIEMENS | Manufacturer Part Number: 3NP5065-1HF13



Manufacturer	SIEMENS
MPN / Reference	3NP5065-1HF13
Catalog number	50651
Category	Fuse switch disconnecter
Minimum order	1 Pcs
Document ID	EO-64BEDF41A9
Generated	2026-08-06

Product Overview

SENTRON, Fuse switch disconnecter 3NP5, 3-pole, NH00, 160 A, with Adapter for Busbar system 8US 40 mm, with high-speed closing, screw terminal, Fuse monitoring: electronic, Auxiliary switch at Switch disconnecter: 1 NO+1 NC, Auxiliary switch at the Fuse monitoring: 2 NO+1 NC

DISCONNECTORS WITH FUSES UNDER LOAD WITH ADAPTER FOR 40MM 3POLOS SYSTEM, I=160A, U=400/500V, AC AUXILIARY CONTACT BLOCK 1NA+1NC NH00 FUSE SIZE WITH FLAT CONNECTION WITH MOUNTED CEF, WITH OWN POWER (INCL. CONTROL CABLE 1M) BLOCK OF AUXILIARY CONTACTS 2NA+2NC. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > POWER DISTRIBUTION AND LOW VOLTAGE SWITCHGEAR > SWITCHES-DISCONNECTORS

Additional Product Information

Technical data

SENTRON, Fuse switch disconnecter 3NP5, 3-pole, NH00, 160 A, with Adapter for Busbar system 8US 40 mm, with high-speed closing, screw terminal, Fuse monitoring: electronic, Auxiliary switch at Switch disconnecter: 1 NO+1 NC, Auxiliary switch at the Fuse monitoring: 2 NO+1 NC

Model

product brand name SENTRON

product designation 3NP5 fuse switch disconnecter

design of the product auxiliary switch at the switch disconnecter: 1 NO + 1 NC, auxiliary switch at the fuse monitoring device: 2NO+1NC

design of the safety monitoring Electronic

design of the actuating element Cover handle

design of the load switch / strip form No

General technical data

number of poles 3

size of disconnecting link NH000, NH00

size of fuse link NH000, NH00

mounting type Plug-in

fuse system LV HRC fuse

Voltage

insulation voltage / rated value 690 V

surge voltage resistance / rated value 6 kV

operating voltage

? at AC / rated value / maximum 690 V

? at DC / rated value 440 V

Protection class

protection class IP / on the front IP00

Dissipation

power loss [W] / for rated value of the current / at AC / in hot operating state / per pole 2.66 W

Current

operational current

? at 35 °C / rated value 160 A

? at 40 °C / rated value 157 A

? at 45 °C / rated value 154 A

? at 50 °C / rated value 152 A

? at 55 °C / rated value 149 A

? at 60 °C / rated value 144 A

? at 65 °C / rated value 136 A

? at 70 °C / rated value 128 A

Main circuit

operational current / rated value 160 A

Suitability

suitability for use...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3NP5065-1HF13 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.