

INDUSTRIAL COMPONENT DATA

3RA1130-4DB34-0AB0 SIEMENS Load feeder fuseless direct-on-line starting, 400 V AC 18...25 A, 24 V AC 50 Hz S..

Brand: SIEMENS | Manufacturer Part Number: 3RA1130-4DB34-0AB0



Manufacturer	SIEMENS
MPN / Reference	3RA1130-4DB34-0AB0
Catalog number	11304
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-0F8A63D8C2
Generated	2026-08-04

Product Overview

Load feeder fuseless direct-on-line starting, 400 V AC 18...25 A, 24 V AC 50 Hz Size S2 Screw terminal on adapter Screw and snap-on mounting Type of coordination 2, Iq = 50 kA (also fulfills type of coordination 1) !!! Phased-out product !!!
Successor is SIRIUS 3RA2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors

Additional Product Information

ETIM: EC001037 - Motor starter/Motor starter combination

Value Unit

Supporting protocol for LON (EF003017) -

Supporting protocol for TCP/IP (EF003050) -

Rated power, 460 V, 60 Hz, 3-phase (EF009600) - kW

Supporting protocol for Foundation Fieldbus (EF007522) -

Supporting protocol for Data-Highway (EF003058) -

Supporting protocol for AS-Interface Safety at Work (EF007519) -

Rated conditional short-circuit current, type 1, 480 Y/277 V (EF009607) - A

Rated power, 575 V, 60 Hz, 3-phase (EF009601) - kW

Supporting protocol for EtherNet/IP (EF007521) -

Supporting protocol for CAN (EF003053) -

Rated conditional short-circuit current, type 1, 600 Y/347 V (EF009608) - A

Suitable for emergency stop (EF001433) -
Ambient temperature, upper operating limit (EF009603) - °C
Supporting protocol for PROFI-safe (EF007526) -
Supporting protocol for PROFINET IO (EF007525) -
Supporting protocol for DeviceNet (EF003059) -
Number of command positions (EF001372) -
Supporting protocol for Modbus (EF003057) -
Degree of protection (NEMA) (EF011959) -
Rated conditional short-circuit current, type 2, 400 V (EF009605) - A
Supporting protocol for DeviceNet Safety (EF007520) -
Type of electrical connection for auxiliary- and control current circuit (EF006979) -
Supporting protocol for SERCOS (EF006657) -
Rail mounting possible (EF003972) -
Supporting protocol for SUCONET (EF003060) -
Rated conditional short-circuit current, type 2, 230 V (EF009606) - A
Supporting protocol for PROFINET CBA (EF007524) -
Suppor...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA1130-4DB34-0AB0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.