

INDUSTRIAL COMPONENT DATA

3RA1130-4FB35-0AF0 SIEMENS Load feeder fuseless direct-on-line starting, 400 V AC 28...40 A, 110 V AC 50 Hz ..

Brand: SIEMENS | Manufacturer Part Number: 3RA1130-4FB35-0AF0



Manufacturer	SIEMENS
MPN / Reference	3RA1130-4FB35-0AF0
Catalog number	11304
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-C7D8CD0430
Generated	2026-08-04

Product Overview

Load feeder fuseless direct-on-line starting, 400 V AC 28...40 A, 110 V AC 50 Hz Size S2 Screw terminal on adapter Screw and snap-on mounting Type of coordination 2, Iq = 50 kA (also fulfills type of coordination 1) !!! Phased-out product !!!
 Successor is SIRIUS 3RA2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors**

Additional Product Information

ETIM: EC001037 - Motor starter/Motor starter combination
 Value Unit
 Supporting protocol for PROFIBUS (EF003052) -
 Rail mounting possible (EF003972) -
 Supporting protocol for AS-Interface Safety at Work (EF007519) -
 Degree of protection (NEMA) (EF011959) -
 Rated power, 460 V, 60 Hz, 3-phase (EF009600) - kW
 Supporting protocol for SUCONET (EF003060) -
 Supporting protocol for DeviceNet (EF003059) -
 Supporting protocol for Data-Highway (EF003058) -
 Supporting protocol for INTERBUS (EF003054) -
 Supporting protocol for TCP/IP (EF003050) -
 Temperature compensated overload protection (EF009604) -

Rated operation power at AC-3, 230 V, 3-phase (EF009599) - kW
Supporting protocol for PROFINET IO (EF007525) -
Supporting protocol for PROFINET CBA (EF007524) -
Supporting protocol for Foundation Fieldbus (EF007522) -
Supporting protocol for DeviceNet Safety (EF007520) -
Supporting protocol for SERCOS (EF006657) -
Supporting protocol for other bus systems (EF003062) -
Ambient temperature, upper operating limit (EF009603) - °C
Supporting protocol for EtherNet/IP (EF007521) -
Rated conditional short-circuit current, type 1, 600 Y/347 V (EF009608) - A
Rated conditional short-circuit current, type 1, 480 Y/277 V (EF009607) - A
Rated conditional short-circuit current, type 2, 230 V (EF009606) - A
Rated conditional short-circuit current, type 2, 400 V (EF009605) - A
Supporting protocol for INTERBUS-Safety (EF006662) -
Supporting protocol for PROFIsafe (EF007526) -
Supporting protocol for CAN (EF0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA1130-4FB35-0AF0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.