

## INDUSTRIAL COMPONENT DATA

# 3RA1130-4FB35-0BB4 SIEMENS Load feeder fuseless direct-on-line starting, 400 V AC 28...40 A, 24 V DC Size S2..

Brand: SIEMENS | Manufacturer Part Number: 3RA1130-4FB35-0BB4



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | SIEMENS                                 |
| MPN / Reference | 3RA1130-4FB35-0BB4                      |
| Catalog number  | 11304                                   |
| Category        | Motor starter/Motor starter combination |
| Minimum order   | 1 Pcs                                   |
| Document ID     | EO-B25823385A                           |
| Generated       | 2026-08-03                              |

## Product Overview

Load feeder fuseless direct-on-line starting, 400 V AC 28...40 A, 24 V DC Size S2 Screw terminal on adapter Screw and snap-on mounting Type of coordination 2, Iq = 50 kA (also fulfills type of coordination 1) !!! Phased-out product !!! Successor is SIRIUS 3RA2 Preferred successor type is >>3RA2130-4UA35-0NB3

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors

## Additional Product Information

ETIM: EC001037 - Motor starter/Motor starter combination

Value Unit

Supporting protocol for DeviceNet (EF003059) -

Supporting protocol for EtherNet/IP (EF007521) -

Release class (EF006668) -

Suitable for emergency stop (EF001433) -

Degree of protection (NEMA) (EF011959) -

Rated power, 575 V, 60 Hz, 3-phase (EF009601) - kW

Supporting protocol for PROFINET IO (EF007525) -

Supporting protocol for DeviceNet Safety (EF007520) -

Type of electrical connection for auxiliary- and control current circuit (EF006979) -

Supporting protocol for INTERBUS-Safety (EF006662) -

External reset possible (EF003426) -

Supporting protocol for Data-Highway (EF003058) -  
Supporting protocol for LON (EF003017) -  
Rated conditional short-circuit current, type 1, 480 Y/277 V (EF009607) - A  
Supporting protocol for SafetyBUS p (EF007527) -  
Supporting protocol for other bus systems (EF003062) -  
Supporting protocol for Modbus (EF003057) -  
Supporting protocol for SERCOS (EF006657) -  
Rail mounting possible (EF003972) -  
Supporting protocol for SUCONET (EF003060) -  
Number of command positions (EF001372) -  
Temperature compensated overload protection (EF009604) -  
Rated operation power at AC-3, 230 V, 3-phase (EF009599) - kW  
Supporting protocol for PROFINET CBA (EF007524) -  
Supporting protocol for Foundation Fieldbus (EF007522) -  
Supporting protocol for TCP/IP (EF003050) -  
Supporting protocol for INTERBUS (EF003054) -  
Ambient temperature, upper operating limit (EF009603) - °C  
Rated conditional short-circuit current,...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA1130-4FB35-0BB4 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.