

INDUSTRIAL COMPONENT DATA

3RA1135-4FB35-0EL2 SIEMENS LOAD FEEDER FUSE LINE DIRECT START, 400 V AC, SIZE S2 28...40 A, 230 V AC, 50 HZ,..

Brand: SIEMENS | Manufacturer Part Number: 3RA1135-4FB35-0EL2



Manufacturer	SIEMENS
MPN / Reference	3RA1135-4FB35-0EL2
Catalog number	11354
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-5F2CD7DDA9
Generated	2026-08-05

Product Overview

LOAD FEEDER FUSE LINE DIRECT START, 400 V AC, SIZE S2 28...40 A, 230 V AC, 50 HZ, SCREW CONNECTION 1NO+1NC (CIRCUIT-BREAKER) FOR SCREW AND SNAP FIXING ASSIGN. TYPE 2, IQ = 50 KA (COMPLY ALSO ASSIGN. TYPE 1)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors
--------------	--

Additional Product Information

product brand name SIRIUS
Product designation non-fused load feeder
Design of the product direct starter
Manufacturer's article number
? of the supplied contactor 3RT1035-1AL20
? of the supplied circuit-breakers 3RV1031-4FA10
? of the supplied link module 3RA1931-1AA00
? of the supplied standard mounting rail adapter 3RA1932-1AA00
General technical data:
Size of load feeder S2
Insulation voltage

? rated value 690 V
Degree of pollution 3
Surge voltage resistance rated value 6 kV
Protection class IP
? on the front IP20
Shock resistance 8g
Mechanical service life (switching cycles)
? of contactor typical 10 000 000
Type of assignment 2
Equipment marking
? acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750 Q
? acc. to DIN EN 61346-2 Q
? acc. to DIN EN 81346-2 Q
Ambient conditions:
Installation altitude at height above sea level maximum 2 000 m
Ambient temperature
? during operation -20 ... +70 °C
? during storage -55 ... +80 °C
Main circuit:
Number of poles for main current circuit 3
Design of the switching contact electromechanical
Adjustable pick-up value current of the current-dependent overload release 28 ... 40 A
Type of the motor protection bimetal
Operating voltage
? at AC-3 rated value maximum 400 V
Operating current
? at AC-3
- at 400 V rated value 35 A
Operating power
? at AC-3
- at 400 V rated value 18.5 kW
No-load switching frequency 15 1/s
Control circuit/ Control:
Type of voltage of the control supply voltage AC
Control supply voltage 1 at AC
? at 50...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA1135-4FB35-0EL2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.