

INDUSTRIAL COMPONENT DATA

3RA1135-6EA34-0AR6 SIEMENS Load feeder fuseless direct-on-line starting, 400 V AC 22...32 A, 400 V DC, 50/60..

Brand: SIEMENS | Manufacturer Part Number: 3RA1135-6EA34-0AR6

	Manufacturer	SIEMENS
	MPN / Reference	3RA1135-6EA34-0AR6
	Catalog number	11356
	Category	Motor starter/Motor starter combination
	Minimum order	1 Pcs
	Document ID	EO-72CE6E2FD1
	Generated	2026-08-03

Product Overview

Load feeder fuseless direct-on-line starting, 400 V AC 22...32 A, 400 V DC, 50/60 Hz Size S2 Screw terminal for installation on standard mounting rail Iq = 50 kA 1 NO + 1 NC (circuit breaker) !!! Phased-out product !!! Successor is SIRIUS 3RA2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors
--------------	--

Additional Product Information

ETIM: EC001037 - Motor starter/Motor starter combination
Value Unit
Voltage type for actuating (EF008242) -
Supporting protocol for TCP/IP (EF003050) -
Temperature compensated overload protection (EF009604) -
Height (EF000040) - mm
Number of auxiliary contacts as normally closed contact (EF001377) -
Rated control supply voltage Us at DC (EF003980) - V
Degree of protection (IP) (EF005474) -
Rated operation power at AC-3, 230 V, 3-phase (EF009599) - kW
Ambient temperature, upper operating limit (EF009603) - °C
Rated control supply voltage Us at AC 60HZ (EF003979) - V
Supporting protocol for PROFIBUS (EF003052) -
Supporting protocol for CAN (EF003053) -

Supporting protocol for INTERBUS (EF003054) -
Supporting protocol for Data-Highway (EF003058) -
Supporting protocol for SUCONET (EF003060) -
Supporting protocol for other bus systems (EF003062) -
Rail mounting possible (EF003972) -
Rated control supply voltage U_s at AC 50HZ (EF003978) - V
Supporting protocol for PROFINET IO (EF007525) -
Rated operation current at AC-3, 400 V (EF009602) - A
Rated conditional short-circuit current, type 1, 480 Y/277 V (EF009607) - A
Supporting protocol for Modbus (EF003057) -
Number of command positions (EF001372) -
Supporting protocol for PROFINET CBA (EF007524) -
Type of motor starter (EF009598) -
Rated power, 460 V, 60 Hz, 3-phase (EF009600) - kW
Rated conditional short-circuit current, type 2, 400 V (EF009605) - A
Rated operation current I_e (EF001443) - A
Coordination class according to IEC 60...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA1135-6EA34-0AR6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.