

INDUSTRIAL COMPONENT DATA

3RA1145-6MA45-0AG6 SIEMENS Load feeder fuseless direct-on-line starting, 400 V AC 80...100 A, 110 V AC 50 Hz..

Brand: SIEMENS | Manufacturer Part Number: 3RA1145-6MA45-0AG6



Manufacturer	SIEMENS
MPN / Reference	3RA1145-6MA45-0AG6
Catalog number	11456
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-676ECC5023
Generated	2026-08-04

Product Overview

Load feeder fuseless direct-on-line starting, 400 V AC 80...100 A, 110 V AC 50 Hz Size S3 Screw terminal for installation on standard mounting rail Iq = 50 kA 1 NO + 1 NC (circuit breaker) !!! Phased-out product !!! Successor is SIRIUS 3RA2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors**

Additional Product Information

ETIM: EC001037 - Motor starter/Motor starter combination
Value Unit
Number of auxiliary contacts as normally closed contact (EF001377) -
Suitable for emergency stop (EF001433) -
Temperature compensated overload protection (EF009604) -
Supporting protocol for Modbus (EF003057) -
External reset possible (EF003426) -
Degree of protection (IP) (EF005474) -
Supporting protocol for EtherNet/IP (EF007521) -
Supporting protocol for LON (EF003017) -
Supporting protocol for Data-Highway (EF003058) -
Rated control supply voltage Us at DC (EF003980) - V
Rated operation current Ie (EF001443) - A
Supporting protocol for TCP/IP (EF003050) -

Supporting protocol for PROFIBUS (EF003052) -
Supporting protocol for INTERBUS-Safety (EF006662) -
Type of electrical connection of main circuit (EF006819) -
Coordination class according to IEC 60947-4-3 (EF012390) -
Height (EF000040) - mm
Depth (EF000049) - mm
Supporting protocol for SUCONET (EF003060) -
Supporting protocol for PROFINET CBA (EF007524) -
Ambient temperature, upper operating limit (EF009603) - °C
Width (EF000008) - mm
Rail mounting possible (EF003972) -
Supporting protocol for DeviceNet Safety (EF007520) -
Rated power, 460 V, 60 Hz, 3-phase (EF009600) - kW
Rated operation current at AC-3, 400 V (EF009602) - A
Rated conditional short-circuit current, type 2, 230 V (EF009606) - A
Rated conditional short-circuit current, type 1, 600 V/347 V (EF009608) - A
Degree of protection (NEMA) (EF011959) -
Rated control supply voltage U_s at AC 60HZ (E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA1145-6MA45-0AG6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.