

INDUSTRIAL COMPONENT DATA

3RA1334-8XB30-1AK6 SIEMENS Reversing contactor assembly AC-3, 15 kW/400 V, 3-pole Size S2, Screw terminal 11..

Brand: SIEMENS | Manufacturer Part Number: 3RA1334-8XB30-1AK6



Manufacturer	SIEMENS
MPN / Reference	3RA1334-8XB30-1AK6
Catalog number	13348
Category	Combination of contactors
Minimum order	1 Pcs
Document ID	EO-2118C62055
Generated	2026-08-06

Product Overview

Reversing contactor assembly AC-3, 15 kW/400 V, 3-pole Size S2, Screw terminal 110 V AC 50 Hz/120 V AC 60 Hz
Electrical and mechanical interlock !!! Phased-out product !!! Successor is SIRIUS 3RA2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors

Additional Product Information

ETIM: EC000010 - Combination of contactors

Value Unit

Degree of protection (NEMA) (EF011959) -

Rated operation power NEMA (EF011960) - kW

Function (EF000030) Reversing contactor

Rated control supply voltage Us at AC 50HZ (EF003978) ['- ', '120'] V

Rated control supply voltage Us at AC 60HZ (EF003979) ['- ', '120'] V

Rated control supply voltage Us at DC (EF003980) ['- ', '-'] V

Voltage type for actuating (EF008242) AC

Rated operation current Ie at AC-3, 400 V (EF001392) 32 A

Rated operation power at AC-3, 400 V (EF001364) 15.0 kW

Type of electrical connection of main circuit (EF006819) Screw connection

Degree of protection (IP) (EF005474) IP20

Reversing contactor assembly AC-3, 15 kW/400 V, 3-pole Size S2, Screw terminal 110 V AC 50 Hz/120 V AC 60 Hz

Electrical and mechanical interlock !!! Phased-out product !!! Successor is SIRIUS 3RA2

Size of contactor S2

Product function Reversing contactor

protection class IP on the front IP20

Reference code acc. to DIN EN 81346-2 Q

Ambient temperature

? during operation -25 ... +60 °C

Operating current

? at AC-3 at 400 V rated value 32 A

Operating power at AC-3 at 400 V rated value 15 kW

Type of voltage of the control supply voltage AC

Control supply voltage 1 at AC

? at 50 Hz rated value 120 V

? at 60 Hz rated value 120 V

control supply voltage frequency

? 1 rated value 60 Hz

? 2 rated value 60 Hz

Number of NC contacts for auxiliary contacts per direction of rotation 0

Number of NO contacts for auxiliary contacts per direction of rotation...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA1334-8XB30-1AK6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.