

INDUSTRIAL COMPONENT DATA

3RA1444-8XC21-1AB0 SIEMENS Contactor assembly Star-delta (wye-delta) (pre-assembled) with lateral timing rel..

Brand: SIEMENS | Manufacturer Part Number: 3RA1444-8XC21-1AB0



Manufacturer	SIEMENS
MPN / Reference	3RA1444-8XC21-1AB0
Catalog number	14448
Category	Combination of contactors
Minimum order	1 Pcs
Document ID	EO-7DF5F3D924
Generated	2026-08-04

Product Overview

Contactor assembly Star-delta (wye-delta) (pre-assembled) with lateral timing relay AC-3, 55 kW/400 V, 3-pole Size S3, S3, S2 Electrically interlocked Screw terminal 24 V AC, 50/60 Hz !!! Phased-out product !!! Successor is SIRIUS 3RA2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors
--------------	--

Additional Product Information

ETIM: EC000010 - Combination of contactors

Value Unit

Rated operation power NEMA (EF011960) - kW

Degree of protection (NEMA) (EF011959) -

Function (EF000030) Star-delta contactor

Rated control supply voltage Us at AC 50HZ (EF003978) ['- ', '24'] V

Rated control supply voltage Us at AC 60HZ (EF003979) ['- ', '24'] V

Rated control supply voltage Us at DC (EF003980) ['- ', '-'] V

Voltage type for actuating (EF008242) AC

Rated operation current Ie at AC-3, 400 V (EF001392) 115 A

Rated operation power at AC-3, 400 V (EF001364) 55.0 kW

Type of electrical connection of main circuit (EF006819) Screw connection

Degree of protection (IP) (EF005474) IP20

Contactor assembly Star-delta (wye-delta) (pre-assembled) with lateral timing relay AC-3, 55 kW/400 V, 3-pole Size S3, S3,

S2 Electrically interlocked Screw terminal 24 V AC, 50/60 Hz !!! Phased-out product !!! Successor is SIRIUS 3RA2

product brand name SIRIUS

Product designation contactor assembly

Size of contactor S3, S3, S2

Product function wye-delta-contactor

Product extension Auxiliary switch Yes

Insulation voltage with degree of pollution 3 at AC rated value 690 V

Degree of pollution 3

protection class IP on the front IP20

Reference code acc. to DIN EN 81346-2 Q

Installation altitude at height above sea level maximum 2 000 m

Ambient temperature

? during operation -25 ... +60 °C

? during storage -55 ... +80 °C

? during transport -55 ... +80 °C

Number of poles for main current circuit 3

Number of NC contacts for main contacts 0

Opera...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA1444-8XC21-1AB0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.