

**INDUSTRIAL COMPONENT DATA**

# 3RA1444-8XC21-1AG2 SIEMENS Contactor assembly Star-delta (wye-delta) (pre-assembled) with lateral timing rel..

Brand: SIEMENS | Manufacturer Part Number: 3RA1444-8XC21-1AG2



|                 |                           |
|-----------------|---------------------------|
| Manufacturer    | SIEMENS                   |
| MPN / Reference | 3RA1444-8XC21-1AG2        |
| Catalog number  | 14448                     |
| Category        | Combination of contactors |
| Minimum order   | 1 Pcs                     |
| Document ID     | EO-3A902EA61B             |
| Generated       | 2026-08-03                |

## Product Overview

Contactor assembly Star-delta (wye-delta) (pre-assembled) with lateral timing relay AC-3, 55 kW/400 V, 3-pole Size S3, S3, S2 Electrically interlocked Screw terminal 110 V AC, 50/60 Hz !!! Phased-out product !!! Successor is SIRIUS 3RA2 Preferred successor type is >>3RA2437-8XF32-1AG2

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors**

## Additional Product Information

ETIM: EC000010 - Combination of contactors  
Value Unit  
Degree of protection (NEMA) (EF011959) -  
Rated operation power NEMA (EF011960) - kW  
Function (EF000030) Star-delta contactor  
Rated control supply voltage Us at AC 50HZ (EF003978) ['- ', '110'] V  
Rated control supply voltage Us at AC 60HZ (EF003979) ['- ', '110'] V  
Rated control supply voltage Us at DC (EF003980) ['- ', '-'] V  
Voltage type for actuating (EF008242) AC  
Rated operation current Ie at AC-3, 400 V (EF001392) 115 A  
Rated operation power at AC-3, 400 V (EF001364) 55.0 kW  
Type of electrical connection of main circuit (EF006819) Screw connection  
Degree of protection (IP) (EF005474) IP20

Contactor assembly Star-delta (wye-delta) (pre-assembled) with lateral timing relay AC-3, 55 kW/400 V, 3-pole Size S3, S3, S2 Electrically interlocked Screw terminal 110 V AC, 50/60 Hz !!! Phased-out product !!! Successor is SIRIUS 3RA2 Preferred successor type is >>3RA2437-8XF32-1AG2

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA1444-8XC21-1AG2 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.