

INDUSTRIAL COMPONENT DATA

3RA2110-1HD16-1BB4 SIEMENS FUSELESS LOAD FEEDER DIRECT START, AC 400V, SZ. S00 5.5. .8A, DC 24V SCREW TERM..

Brand: SIEMENS | Manufacturer Part Number: 3RA2110-1HD16-1BB4



Manufacturer	SIEMENS
MPN / Reference	3RA2110-1HD16-1BB4
Catalog number	21101
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-9CBB2C2E41
Generated	2026-08-04

Product Overview

FUSELESS LOAD FEEDER DIRECT START, AC 400V, SZ. S00 5.5. .8A, DC 24V SCREW TERMINAL FOR BUSBAR SYSTEMS 60MM TYPE OF ASSIGNMENT 1,IQ = 150KA 1NO (CONTACTOR)
DERIVATION TO MOTOR WITHOUT FUSES ARRANQ. DIREC, AC 400V, TAM. S00 5.5. .8A, DC 24V SCREW TERMINALS FOR 60MM BUSBARS COORD TYPE. 1,IQ = 150KA 1NA (CONTACTOR). Manufactured to order.
Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors
--------------	--

Additional Product Information

Technical data

FUSELESS LOAD FEEDER DIRECT START, AC 400V, SZ. S00 5.5. .8A, DC 24V SCREW TERMINAL FOR BUSBAR SYSTEMS 60MM TYPE OF ASSIGNMENT 1,IQ = 150KA 1NO (CONTACTOR)

product brand name SIRIUS

product designation Direct (on-line) starter

design of the product for 60 mm busbars

product type designation 3RA21

manufacturer's article number

? of the supplied contactor 3RT2016-1BB41

? of the supplied circuit-breakers 3RV2011-1HA10
? of the supplied busbar adapter 8US1251-5DS10
? of the supplied link module 3RA1921-1DA00
General technical data
size of the circuit-breaker S00
size of load feeder S00
insulation voltage with degree of pollution 3 at AC rated value 690 V
surge voltage resistance rated value 6 kV
degree of protection NEMA rating other
shock resistance according to IEC 60068-2-27 6g / 11 ms
mechanical service life (switching cycles) of contactor typical 30 000 000
type of assignment 1
type of protection according to ATEX directive 2014/34/EU Ex II (2) GD
certificate of suitability according to ATEX directive 2014/34/EU DMT 02 ATEX F 001
Substance Prohibitance (Date) 10/01/2009
Ambient conditions
ambient temperature
? during operation -20 ... +60 °C
? during storage -50 ... +80 °C
? during transport -50 ... +80 °C
temperature compensation -20 ... +60 °C
relative humidity during operation 10 ... 95 %
Main circuit
number of poles for main current circuit 3
design of the switching contact electromechanical
adjustable current response value current of the current-depen...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA2110-1HD16-1BB4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.