

INDUSTRIAL COMPONENT DATA

3RA2115-1EA16-5BB4 SIEMENS Load feeder fuseless, Direct-on-line starting 400 V AC, Size S00 2.80...4.00 A 24..

Brand: SIEMENS | Manufacturer Part Number: 3RA2115-1EA16-5BB4



Manufacturer	SIEMENS
MPN / Reference	3RA2115-1EA16-5BB4
Catalog number	21151
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-54A838FA5E
Generated	2026-08-04

Product Overview

Load feeder fuseless, Direct-on-line starting 400 V AC, Size S00 2.80...4.00 A 24 V DC screw terminal for installation on standard mounting rail (also fulfills type of coordination 1) Type of coordination 2, Iq = 150 kA 1 NC (contactor) 1 NO+1 NC (circuit breaker, transverse)

DERIVAC. A MOTOR WITHOUT FUSES ARR. DIRECT, AC 400V, TAM. S00 2,80...4,00A 4KW,24 V DC SCREW TERMINALS FOR MOUNTING ON DIN PROFILE, (ALSO COMPLIES TYPE COORD. 1) TYPE OF COORD. 2,IQ = 150KA 1NC (CONTACTOR) 1NA+1NC (INTERR. AUTO, TRANSV.). Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors**

Additional Product Information

Technical data

Load feeder fuseless, Direct-on-line starting 400 V AC, Size S00 2.80...4.00 A 24 V DC screw terminal for installation on standard mounting rail (also fulfills type of coordination 1) Type of coordination 2, Iq = 150 kA 1 NC (contactor) 1 NO+1 NC (circuit breaker, transverse)

product brand name SIRIUS

product designation Direct (on-line) starter

design of the product for standard rail or screw mounting

product type designation 3RA21

manufacturer's article number

? of the supplied contactor 3RT2016-1BB44

? of the supplied circuit-breakers 3RV2011-1EA15
? of the supplied link module 3RA1921-1DA00
General technical data
size of the circuit-breaker S00
size of load feeder S00
power loss [W] for rated value of the current
? at AC in hot operating state per pole 2.7 W
? without load current share typical 4 W
insulation voltage with degree of pollution 3 at AC rated value 690 V
surge voltage resistance rated value 6 kV
degree of protection NEMA rating other
shock resistance according to IEC 60068-2-27 6g / 11 ms
mechanical service life (operating cycles) of contactor typical 30 000 000
type of assignment 2
type of protection according to ATEX directive 2014/34/EU Ex II (2) GD
certificate of suitability according to ATEX directive 2014/34/EU DMT 02 ATEX F 001
reference code according to IEC 81346-2:2019 Q
Ambient conditions
ambient temperature
? during operation -20 ... +60 °C
? during storage -50 ... +80 °C
? during transport -50 ... +80 °C
temperature compensation -...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA2115-1EA16-5BB4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.