

INDUSTRIAL COMPONENT DATA

3RA2150-4XA37-0AP0 SIEMENS Load feeder fuseless, Direct-on-line starting 400 V AC, Size S2 49...59 A 230 V A..

Brand: SIEMENS | Manufacturer Part Number: 3RA2150-4XA37-0AP0



Manufacturer	SIEMENS
MPN / Reference	3RA2150-4XA37-0AP0
Catalog number	21504
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-9C75146AD0
Generated	2026-08-04

Product Overview

Load feeder fuseless, Direct-on-line starting 400 V AC, Size S2 49...59 A 230 V AC, 50 Hz screw terminal for installation on standard mounting rail (also fulfills type of coordination 1) Type of coordination 2, Iq = 150 kA 1 NO+1 NC (contactor) DERIVAC. MOTOR WITHOUT FUSES ARR. DIRECT, AC 400V, TAM. S2 49 ... 59A 230V AC 50HZ SCREW TERMINALS FOR MOUNTING ON DIN PROFILE, (ALSO COMPLIES WITH TYPE COORD. 1) TYPE OF COORD. 2, Iq = 150KA 1NA+1NC (CONTACTOR).

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors

Additional Product Information

Technical data

Load feeder fuseless, Direct-on-line starting 400 V AC, Size S2 49...59 A 230 V AC, 50 Hz screw terminal for installation on standard mounting rail (also fulfills type of coordination 1) Type of coordination 2, Iq = 150 kA 1 NO+1 NC (contactor)

product brand name SIRIUS

product designation Direct (on-line) starter

design of the product for standard rail or screw mounting

product type designation 3RA21

manufacturer's article number

? of the supplied contactor 3RT2037-1AP00

? of the supplied circuit-breakers 3RV2032-4XA10

? of the supplied link module 3RA2931-1AA00

General technical data

size of the circuit-breaker S2

size of load feeder S2

insulation voltage with degree of pollution 3 at AC rated value 690 V

surge voltage resistance rated value 6 kV

degree of protection NEMA rating other

shock resistance according to IEC 60068-2-27 6g / 11 ms

mechanical service life (switching cycles) of contactor typical 10 000 000

type of assignment 2

type of protection according to ATEX directive 2014/34/EU Ex II (2) GD

certificate of suitability according to ATEX directive 2014/34/EU DMT 02 ATEX F 001

Substance Prohibitance (Date) 03/01/2017

Ambient conditions

ambient temperature

? during operation -20 ... +60 °C

? during storage -50 ... +80 °C

? during transport -50 ... +80 °C

temperature compensation -20 ... +60 °C

relative humidity during operation 10 ... 95 %

Main circuit

number of poles for main current circuit 3

design of the switching contact electromechanical

adjust...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA2150-4XA37-0AP0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.