

INDUSTRIAL COMPONENT DATA

3RA2210-1HA16-2BB4 SIEMENS FUSELESS LOAD FEEDER REVERSING OPERATION, AC 400V, S00 5.5. .8A, 4KW, DC 24V SC..

Brand: SIEMENS | Manufacturer Part Number: 3RA2210-1HA16-2BB4



Manufacturer	SIEMENS
MPN / Reference	3RA2210-1HA16-2BB4
Catalog number	22101
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-94682B76F5
Generated	2026-08-05

Product Overview

FUSELESS LOAD FEEDER REVERSING OPERATION, AC 400V, S00 5.5. .8A, 4KW, DC 24V SCREW TERMINAL FOR RAIL MOUNTING, TYPE OF ASSIGNMENT 1,IQ = 150KA 1NC (CONTACTOR)
SHUNT TO MOTOR WITHOUT INVERTER FUSES, AC 400V, S00 5.5. .8A, DC 24V SCREW TERMINALS FOR FIXING ON DIN PROFILE, TYPE OF COORD. 1,IQ = 150KA 1NC (CONTACTOR). Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors**

Additional Product Information

Technical data

FUSELESS LOAD FEEDER REVERSING OPERATION, AC 400V, S00 5.5. .8A, 4KW, DC 24V SCREW TERMINAL FOR RAIL MOUNTING, TYPE OF ASSIGNMENT 1,IQ = 150KA 1NC (CONTACTOR)

product brand name SIRIUS

product designation Reversing starter

design of the product for standard rail or screw mounting

product type designation 3RA22

manufacturer's article number

? of the supplied contactor 3RT2016-1BB42

? of the supplied circuit-breakers 3RV2011-1HA10

? of the supplied link module 3RA1921-1DA00

General technical data

size of the circuit-breaker S00

size of load feeder S00

insulation voltage with degree of pollution 3 at AC rated value 690 V

surge voltage resistance rated value 6 kV

degree of protection NEMA rating other

shock resistance according to IEC 60068-2-27 6g / 11 ms

mechanical service life (switching cycles) of contactor typical 30 000 000

type of assignment 1

type of protection according to ATEX directive 2014/34/EU Ex II (2) GD

certificate of suitability according to ATEX directive 2014/34/EU DMT 02 ATEX F 001

Substance Prohibitance (Date) 10/01/2009

Ambient conditions

ambient temperature

? during operation -20 ... +60 °C

? during storage -50 ... +80 °C

? during transport -50 ... +80 °C

temperature compensation -20 ... +60 °C

relative humidity during operation 10 ... 95 %

Main circuit

number of poles for main current circuit 3

design of the switching contact electromechanical

adjustable current response value current of the current-dependent overload release 5.5 ... 8 A...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA2210-1HA16-2BB4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.