INDUSTRIAL COMPONENT DATA

3RA2210-4AD18-2AP0 SIEMENS Load feeder fuseless, Reversing duty 400 V AC, Size S00 10.0...16.0 A 230 V AC sc..

Brand: SIEMENS | Manufacturer Part Number: 3RA2210-4AD18-2AP0

Manufacturer	SIEMENS
MPN / Reference	3RA2210-4AD18-2AP0
Catalog number	22104
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-208ACF7744
Generated	2026-08-06

Product Overview

Load feeder fuseless, Reversing duty 400 V AC, Size S00 10.0...16.0 A 230 V AC screw terminal for 60 mm busbar systems Type of coordination 1, Iq = 150 kA 1 NC (contactor)
SIRIUS Innovations Bypass to Inverter Motor, AC 400V, S00, 11. . .16A, AC 230V screw connection 1NC fixing muddy 60mm. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors

Additional Product Information

Technical data
Load feeder fuseless, Reversing duty 400 V AC, Size S00 10.0...16.0 A 230 V AC screw terminal for 60 mm busbar systems Type of coordination 1, Iq = 150 kA 1 NC (contactor)
product brand name SIRIUS
product designation Reversing starter
design of the product for 60 mm busbars
product type designation 3RA22
manufacturer's article number
? of the supplied contactor 3RT2018-1AP02
? of the supplied circuit-breakers 3RV2011-4AA10
? of the supplied RS assembly kit 8US1250-5AS10
? of the supplied busbar adapter 8US1251-5DS10

? of the supplied link module 3RA1921-1DA00
General technical data
size of the circuit-breaker S00
size of load feeder S00
insulation voltage with degree of pollution 3 at AC rated value 690 V
surge voltage resistance rated value 6 kV
degree of protection NEMA rating other
shock resistance according to IEC 60068-2-27 6g / 11 ms
mechanical service life (switching cycles) of contactor typical 30 000 000
type of assignment 1
type of protection according to ATEX directive 2014/34/EU Ex II (2) GD
certificate of suitability according to ATEX directive 2014/34/EU DMT 02 ATEX F 001
Substance Prohibitance (Date) 10/01/2009
Ambient conditions
ambient temperature
? during operation -20 ... +60 °C
? during storage -50 ... +80 °C
? during transport -50 ... +80 °C
temperature compensation -20 ... +60 °C
relative humidity during operation 10 ... 95 %
Main circuit
number of poles for main current circuit 3
design of the switching contact electromechanical
adjusta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA2210-4AD18-2AP0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.