

**INDUSTRIAL COMPONENT DATA**

# 3RA2220-4NH27-0BB4 SIEMENS Load feeder fuseless, Reversing duty 400 V AC, Size S0 23.0...28.0 A 24 V DC Spri..

Brand: SIEMENS | Manufacturer Part Number: 3RA2220-4NH27-0BB4



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | SIEMENS                                 |
| MPN / Reference | 3RA2220-4NH27-0BB4                      |
| Catalog number  | 22204                                   |
| Category        | Motor starter/Motor starter combination |
| Minimum order   | 1 Pcs                                   |
| Document ID     | EO-51AAFBF6ED                           |
| Generated       | 2026-08-05                              |

## Product Overview

Load feeder fuseless, Reversing duty 400 V AC, Size S0 23.0...28.0 A 24 V DC Spring-type terminal for 60 mm busbar systems (also fulfills type of coordination 1) Type of coordination 2, Iq = 150 kA 1 NO+1 NC (contactor) DERIVAC. A MOTOR WITHOUT FUSES FOR INVESTMENT, AC 400V, BGR. S0, 23...28A, DC 24V SPRING TERMINALS FOR 60MM BUSBARS COORD TYPE. 2,IQ = 150KA (MEETS TAMB. TYPE OF COORD. 1) 1NA+1NC (CONTACTOR). Manufactured to order. Non-Cancelable Non-Returnable.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors**

## Additional Product Information

**Technical data**

Load feeder fuseless, Reversing duty 400 V AC, Size S0 23.0...28.0 A 24 V DC Spring-type terminal for 60 mm busbar systems (also fulfills type of coordination 1) Type of coordination 2, Iq = 150 kA 1 NO+1 NC (contactor)  
product brand name SIRIUS  
product designation Reversing starter  
design of the product for 60 mm busbars  
product type designation 3RA22  
manufacturer's article number  
? of the supplied contactor 3RT2027-2BB40  
? of the supplied circuit-breakers 3RV2021-4NA20  
? of the supplied RS assembly kit 8US1250-5AT10

? of the supplied busbar adapter 8US1251-5NT11  
? of the supplied link module 3RA2921-2AA00  
General technical data  
size of the circuit-breaker S0  
size of load feeder S0  
insulation voltage with degree of pollution 3 at AC rated value 690 V  
surge voltage resistance rated value 6 kV  
degree of protection NEMA rating other  
shock resistance according to IEC 60068-2-27 6g / 11 ms  
mechanical service life (switching cycles) of contactor typical 10 000 000  
type of assignment 2  
type of protection according to ATEX directive 2014/34/EU Ex II (2) GD  
certificate of suitability according to ATEX directive 2014/34/EU DMT 02 ATEX F 001  
Substance Prohibitance (Date) 10/01/2009  
Ambient conditions  
ambient temperature  
? during operation -20 ... +60 °C  
? during storage -50 ... +80 °C  
? during transport -50 ... +80 °C  
temperature compensation -20 ... +60 °C  
relative humidity during operation 10 ... 95 %  
Main circuit  
number of poles for main current circuit 3  
design of t...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA2220-4NH27-0BB4 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.