

INDUSTRIAL COMPONENT DATA

3RA2317-8XB11-5BB4 SIEMENS reversing contactor assembly, AC-3e/AC-3, 12 A, 5.5 kW / 400 V, 3-pole, 24 V DC, ..

Brand: SIEMENS | Manufacturer Part Number: 3RA2317-8XB11-5BB4



Manufacturer	SIEMENS
MPN / Reference	3RA2317-8XB11-5BB4
Catalog number	23178
Category	Combination of contactors
Minimum order	1 Pcs
Document ID	EO-F3BE41D034
Generated	2026-08-05

Product Overview

reversing contactor assembly, AC-3e/AC-3, 12 A, 5.5 kW / 400 V, 3-pole, 24 V DC, solder pin connection, mechanical interlock with main current path wiring, without wiring of coil control

COMB. CONTACTORS P/ INVERSION AC-3, 5.5KW/400V, 3 POLES, TAM. S00, WELDING PINS, DC 24V, . NO COIL CONTROL WIRING

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors

Additional Product Information

Technical data

reversing contactor assembly, AC-3e/AC-3, 12 A, 5.5 kW / 400 V, 3-pole, 24 V DC, solder pin connection, mechanical interlock with main current path wiring, without wiring of coil control

product brand name SIRIUS

product designation Reversing contactor assembly

product type designation 3RA23

manufacturer's article number

? 1 of the supplied contactor 3RT2017-1BB42

? 2 of the supplied contactor 3RT2017-1BB42

? of the supplied RH assembly kit 3RA2913-2AA1

General technical data

size of contactor S00

product extension auxiliary switch Yes
shock resistance at rectangular impulse
? at AC 7,3g / 5 ms, 4,7g / 10 ms
? at DC 7.3g / 5 ms, 4.7g / 10 ms
shock resistance with sine pulse
? at AC 11,4g / 5 ms, 7,3g / 10 ms
? at DC 11,4g / 5 ms, 7,3g / 10 ms
mechanical service life (operating cycles)
? of contactor typical 10 000 000
? of the contactor with added auxiliary switch block typical 10 000 000
reference code according to IEC 81346-2 Q
Substance Prohibitance (Date) 07/01/2006
Ambient conditions
installation altitude at height above sea level maximum 2 000 m
ambient temperature
? during operation -25 ... +60 °C
? during storage -55 ... +80 °C
Main circuit
number of poles for main current circuit 3
number of NO contacts for main contacts 3
number of NC contacts for main contacts 0
operating voltage
? at AC-3 rated value maximum 690 V
? at AC-3e rated value maximum 690 V
operational current
? at AC-3
- at 400 V rated value 12 A
- at 500 V rated value 9.2 A
- at 690 V r...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA2317-8XB11-5BB4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.