

INDUSTRIAL COMPONENT DATA

3RA2317-8XB30-1AP0 SIEMENS Reversing contactor assembly AC-3, 5.5 kW/400 V,AC230V,50/60Hz 3-pole, Size S00 S..

Brand: SIEMENS | Manufacturer Part Number: 3RA2317-8XB30-1AP0



Manufacturer	SIEMENS
MPN / Reference	3RA2317-8XB30-1AP0
Catalog number	23178
Category	Combination of contactors
Minimum order	1 Pcs
Document ID	EO-76C1BFE9E8
Generated	2026-08-06

Product Overview

Reversing contactor assembly AC-3, 5.5 kW/400 V,AC230V,50/60Hz 3-pole, Size S00 screw terminal electrical and mechanical interlock

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors**

Additional Product Information

Technical data

Reversing contactor assembly AC-3, 5.5 kW/400 V,AC230V,50/60Hz 3-pole, Size S00 screw terminal electrical and mechanical interlock

product brand name SIRIUS

product designation Reversing contactor assembly

product type designation 3RA23

manufacturer's article number

? 1 of the supplied contactor 3RT2017-1AP02

? 2 of the supplied contactor 3RT2017-1AP02

? of the supplied RH assembly kit 3RA2913-2AA1

General technical data

size of contactor S00

product extension auxiliary switch Yes
shock resistance at rectangular impulse
? at AC 7,3g / 5 ms, 4,7g / 10 ms
? at DC 7.3g / 5 ms, 4.7g / 10 ms
shock resistance with sine pulse
? at AC 11,4g / 5 ms, 7,3g / 10 ms
? at DC 11,4g / 5 ms, 7,3g / 10 ms
mechanical service life (switching cycles)
? of contactor typical 10 000 000
? of the contactor with added auxiliary switch block typical 10 000 000
reference code according to IEC 81346-2 Q
Substance Prohibitance (Date) 10/01/2009
Ambient conditions
installation altitude at height above sea level maximum 2 000 m
ambient temperature
? during operation -25 ... +60 °C
? during storage -55 ... +80 °C
Main circuit
number of poles for main current circuit 3
number of NO contacts for main contacts 3
number of NC contacts for main contacts 0
operating voltage at AC-3 rated value maximum 690 V
operational current at AC-3
? at 400 V rated value 12 A
? at 500 V rated value 9.2 A
? at 690 V rated value 6.7 A
operating power
? at AC-3
- at 400 V rated value 5.5 kW
- at 500 V rated value 5...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA2317-8XB30-1AP0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.