

## INDUSTRIAL COMPONENT DATA

# 3RA2324-8XB30-2FB4 SIEMENS Reversing contactor assembly AC-3, 5.5 kW/400 V, 24 V DC 3-pole, Size S0 Spring-t..

Brand: SIEMENS | Manufacturer Part Number: 3RA2324-8XB30-2FB4



|                 |                           |
|-----------------|---------------------------|
| Manufacturer    | SIEMENS                   |
| MPN / Reference | 3RA2324-8XB30-2FB4        |
| Catalog number  | 23248                     |
| Category        | Combination of contactors |
| Minimum order   | 1 Pcs                     |
| Document ID     | EO-4EB2C497BD             |
| Generated       | 2026-08-05                |

## Product Overview

Reversing contactor assembly AC-3, 5.5 kW/400 V, 24 V DC 3-pole, Size S0 Spring-type terminal electrical and mechanical interlock with integrated diode

COMB. INV., AC3, 5,5KW/400V DC 24V 3POL, SIZE S0 SPRING TERMINALS INTERLOCKING ELECTR. AND MEC. 2X 1NA FREE IN AP. BASE .. Manufactured to order. Non-Cancelable Non-Returnable.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors

## Additional Product Information

## Technical data

Reversing contactor assembly AC-3, 5.5 kW/400 V, 24 V DC 3-pole, Size S0 Spring-type terminal electrical and mechanical interlock with integrated diode

product brand name SIRIUS

product designation Reversing contactor assembly

product type designation 3RA23

manufacturer's article number

? 1 of the supplied contactor 3RT2024-2FB40

? 2 of the supplied contactor 3RT2024-2FB40

? of the supplied RH assembly kit 3RA2923-2AA2

**General technical data**

size of contactor S0

product extension auxiliary switch Yes

shock resistance at rectangular impulse

? at AC 7,5g / 5 ms, 4,7g / 10 ms

? at DC 10g / 5 ms, 7,5g / 10 ms

shock resistance with sine pulse

? at AC 11,8g / 5 ms, 7,4g / 10 ms

? at DC 15g / 5 ms, 10g / 10 ms

mechanical service life (switching cycles)

? of contactor typical 10 000 000

? of the contactor with added auxiliary switch block typical 10 000 000

reference code according to IEC 81346-2 Q

Substance Prohibitance (Date) 10/01/2009

Ambient conditions

installation altitude at height above sea level maximum 2 000 m

ambient temperature

? during operation -25 ... +60 °C

? during storage -55 ... +80 °C

Main circuit

number of poles for main current circuit 3

number of NO contacts for main contacts 3

number of NC contacts for main contacts 0

operating voltage at AC-3 rated value maximum 690 V

operational current at AC-3

? at 400 V rated value 12 A

? at 500 V rated value 12 A

? at 690 V rated value 9 A

operating power

? at AC-3

- at 400 V rated value 5.5 kW

- at 500 V....

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send SIEMENS / 3RA2324-8XB30-2FB4 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.