

INDUSTRIAL COMPONENT DATA

3RA2335-8XB30-1AP6 SIEMENS Reversing contactor assembly, AC-3, 18.5 kW 400 V, 220 V AC/50 Hz/240 V AC/60 Hz ..

Brand: SIEMENS | Manufacturer Part Number: 3RA2335-8XB30-1AP6



Manufacturer	SIEMENS
MPN / Reference	3RA2335-8XB30-1AP6
Catalog number	23358
Category	Combination of contactors
Minimum order	1 Pcs
Document ID	EO-611BC242B4
Generated	2026-08-06

Product Overview

Reversing contactor assembly, AC-3, 18.5 kW 400 V, 220 V AC/50 Hz/240 V AC/60 Hz 3-pole, Size S2 screw terminal electrical and mechanical interlock 2 NO integrated
 COMB. INV., AC3:18,5KW/400V, AC 220V 50HZ 240V 60 HZ, 3POL, TAM. S2 INTERLOCK SCREW TERMINALS.
 ELECTRICAL AND MECHANICAL 2NA INTEGRATED. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors**

Additional Product Information

Technical data

Reversing contactor assembly, AC-3, 18.5 kW 400 V, 220 V AC/50 Hz/240 V AC/60 Hz 3-pole, Size S2 screw terminal electrical and mechanical interlock 2 NO integrated
 product brand name SIRIUS
 product designation Reversing contactor assembly
 product type designation 3RA23
 manufacturer's article number
 ? 1 of the supplied contactor 3RT2035-1AG20
 ? 2 of the supplied contactor 3RT2035-1AG20
 ? of the supplied RS assembly kit 3RA2933-2AA1

General technical data

size of contactor S2

product extension auxiliary switch Yes

shock resistance at rectangular impulse

? at AC 11.8g / 5 ms, 11.6g / 10 ms

shock resistance with sine pulse

? at AC 18.5g / 5 ms, 11.6g / 10 ms

mechanical service life (switching cycles)

? of contactor typical 10 000 000

? of the contactor with added auxiliary switch block typical 10 000 000

reference code according to IEC 81346-2 Q

Substance Prohibitance (Date) 10/01/2014

Ambient conditions

installation altitude at height above sea level maximum 2 000 m

ambient temperature

? during operation -25 ... +60 °C

? during storage -55 ... +80 °C

Main circuit

number of poles for main current circuit 3

number of NO contacts for main contacts 3

number of NC contacts for main contacts 0

operating voltage at AC-3 rated value maximum 690 V

operational current at AC-3

? at 400 V rated value 41 A

? at 500 V rated value 41 A

? at 690 V rated value 24 A

operating power

? at AC-3

- at 400 V rated value 18.5 kW

- at 500 V rated value 22 kW

- at 690 V rated value 22 kW

?...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA2335-8XB30-1AP6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.