

INDUSTRIAL COMPONENT DATA

3RA2336-8XB30-1AK6 SIEMENS Reversing contactor assembly AC-3, 22 kW/400 V 110 V AC 50 Hz/120 V 60 Hz, 3-pole..

Brand: SIEMENS | Manufacturer Part Number: 3RA2336-8XB30-1AK6



Manufacturer	SIEMENS
MPN / Reference	3RA2336-8XB30-1AK6
Catalog number	23368
Category	Combination of contactors
Minimum order	1 Pcs
Document ID	EO-1AE2894EA3
Generated	2026-08-06

Product Overview

Reversing contactor assembly AC-3, 22 kW/400 V 110 V AC 50 Hz/120 V 60 Hz, 3-pole Size S2, screw terminal electrical and mechanical Interlock 2 NO integrated
 INVERTER, SIZE S2, 50A, AC-3, 22W / 400V 3 POLES, AC 110-120V 50/60HZ, 2NA INTEGRATED, SCREW TERMINALS, ENCLV. ELECTRICAL AND MECHANICAL.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors**

Additional Product Information

Technical data

Reversing contactor assembly AC-3, 22 kW/400 V 110 V AC 50 Hz/120 V 60 Hz, 3-pole Size S2, screw terminal electrical and mechanical Interlock 2 NO integrated
 product brand name SIRIUS
 product designation Reversing contactor assembly
 product type designation 3RA23
 manufacturer's article number
 ? 1 of the supplied contactor 3RT2036-1AK60
 ? 2 of the supplied contactor 3RT2036-1AK60
 ? of the supplied RS assembly kit 3RA2933-2AA1

General technical data

size of contactor S2

product extension auxiliary switch Yes

shock resistance at rectangular impulse

? at AC 11.8g / 5 ms, 11.6g / 10 ms

shock resistance with sine pulse

? at AC 18.5g / 5 ms, 11.6g / 10 ms

mechanical service life (switching cycles)

? of contactor typical 10 000 000

? of the contactor with added auxiliary switch block typical 10 000 000

reference code according to IEC 81346-2 Q

Substance Prohibitance (Date) 10/01/2014

Ambient conditions

installation altitude at height above sea level maximum 2 000 m

ambient temperature

? during operation -25 ... +60 °C

? during storage -55 ... +80 °C

Main circuit

number of poles for main current circuit 3

number of NO contacts for main contacts 3

number of NC contacts for main contacts 0

operating voltage at AC-3 rated value maximum 690 V

operational current at AC-3

? at 400 V rated value 51 A

? at 500 V rated value 51 A

? at 690 V rated value 24 A

operating power

? at AC-3

- at 400 V rated value 22 kW

- at 500 V rated value 30 kW

- at 690 V rated value 22 kW

? at AC-4...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA2336-8XB30-1AK6 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.