

**INDUSTRIAL COMPONENT DATA**

# 3RA2337-8XB30-1AK6 SIEMENS Reversing contactor assembly AC-3, 30 kW/400 V 110 V AC 50 Hz/120 V 60 Hz, 3-pole..

Brand: SIEMENS | Manufacturer Part Number: 3RA2337-8XB30-1AK6



|                 |                           |
|-----------------|---------------------------|
| Manufacturer    | SIEMENS                   |
| MPN / Reference | 3RA2337-8XB30-1AK6        |
| Catalog number  | 23378                     |
| Category        | Combination of contactors |
| Minimum order   | 1 Pcs                     |
| Document ID     | EO-84AFBE55B5             |
| Generated       | 2026-08-06                |

## Product Overview

Reversing contactor assembly AC-3, 30 kW/400 V 110 V AC 50 Hz/120 V 60 Hz, 3-pole Size S2, screw terminal electrical and mechanical Interlock 2 NO integrated  
 INVERTER, SIZE S2, 65A, AC-3, 30KW / 400V 3 POLES, AC 110-120V 50/60HZ, 2NA INTEGRATED, SCREW TERMINALS, ENCLV. ELECTRICAL AND MECHANICAL. Manufactured to order. Non-Cancelable Non-Returnable.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors**

## Additional Product Information

**Technical data**

Reversing contactor assembly AC-3, 30 kW/400 V 110 V AC 50 Hz/120 V 60 Hz, 3-pole Size S2, screw terminal electrical and mechanical Interlock 2 NO integrated  
 product brand name SIRIUS  
 product designation Reversing contactor assembly  
 product type designation 3RA23  
 manufacturer's article number  
 ? 1 of the supplied contactor 3RT2037-1AK60  
 ? 2 of the supplied contactor 3RT2037-1AK60  
 ? of the supplied RS assembly kit 3RA2933-2AA1

**General technical data**

size of contactor S2

product extension auxiliary switch Yes

shock resistance at rectangular impulse

? at AC 11.8g / 5 ms, 11.6g / 10 ms

shock resistance with sine pulse

? at AC 18.5g / 5 ms, 11.6g / 10 ms

mechanical service life (switching cycles)

? of contactor typical 10 000 000

? of the contactor with added auxiliary switch block typical 10 000 000

reference code according to IEC 81346-2 Q

Substance Prohibitance (Date) 10/01/2014

**Ambient conditions**

installation altitude at height above sea level maximum 2 000 m

ambient temperature

? during operation -25 ... +60 °C

? during storage -55 ... +80 °C

**Main circuit**

number of poles for main current circuit 3

number of NO contacts for main contacts 3

number of NC contacts for main contacts 0

operating voltage at AC-3 rated value maximum 690 V

operational current at AC-3

? at 400 V rated value 65 A

? at 500 V rated value 65 A

? at 690 V rated value 47 A

operating power

? at AC-3

- at 400 V rated value 30 kW

- at 500 V rated value 37 kW

- at 690 V rated value 37 kW

? at AC-4...

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send SIEMENS / 3RA2337-8XB30-1AK6 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.