

INDUSTRIAL COMPONENT DATA

3RA2426-8XF32-1AG2 SIEMENS Contactor assembly for star-delta (wye-delta) start AC-3, 22 kW/400 V, 110 V AC 5..

Brand: SIEMENS | Manufacturer Part Number: 3RA2426-8XF32-1AG2



Manufacturer	SIEMENS
MPN / Reference	3RA2426-8XF32-1AG2
Catalog number	24268
Category	Combination of contactors
Minimum order	1 Pcs
Document ID	EO-C6EAD2136E
Generated	2026-08-06

Product Overview

Contactor assembly for star-delta (wye-delta) start AC-3, 22 kW/400 V, 110 V AC 50/60 Hz, 3-pole, size S0 screw terminals electrical and mechanical interlock 3 NO + 3 NC integrated

SIRIUS Innovations Star-Triangle AC3, 22KW/400V AC 110V, 50/60 HZ, S0, Enclav screw connection. electrical and mechanical. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors**

Additional Product Information

Technical data

Contactor assembly for star-delta (wye-delta) start AC-3, 22 kW/400 V, 110 V AC 50/60 Hz, 3-pole, size S0 screw terminals electrical and mechanical interlock 3 NO + 3 NC integrated

product brand name SIRIUS

product designation Contactor assembly for star-delta (wye-delta) start

product type designation 3RA24

manufacturer's article number

? 1 of the supplied contactor 3RT2027-1AG20

? 2 of the supplied contactor 3RT2027-1AG20

? 3 of the supplied contactor 3RT2026-1AG20

? of the supplied RS assembly kit 3RA2923-2BB1

? of the supplied function module for wye-delta circuits 3RA2816-0EW20

General technical data

size of contactor S0

product extension auxiliary switch No

shock resistance at rectangular impulse

? at AC 8,3g / 5 ms, 5,3g / 10 ms

? at DC 10g / 5 ms, 7,5g / 10 ms

shock resistance with sine pulse

? at AC 13,5g / 5 ms, 8,3g / 10 ms

? at DC 15g / 5 ms, 10g / 10 ms

mechanical service life (switching cycles)

? of contactor typical 10 000 000

? of the contactor with added auxiliary switch block typical 10 000 000

reference code according to IEC 81346-2 Q

Substance Prohibitance (Date) 10/01/2009

Ambient conditions

installation altitude at height above sea level maximum 2 000 m

ambient temperature

? during operation -25 ... +60 °C

? during storage -55 ... +80 °C

Main circuit

number of poles for main current circuit 3

number of NO contacts for main contacts 3

number of NC contacts for main contacts 0

operating voltage at AC-3 rated value maximum 690 V

operational....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA2426-8XF32-1AG2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.