

INDUSTRIAL COMPONENT DATA

3RA2437-8XH32-1NB3 SIEMENS Contactor assembly for star-delta (wye-delta) start, AS-i AC-3, 55 kW/400 V, 20-3..

Brand: SIEMENS | Manufacturer Part Number: 3RA2437-8XH32-1NB3



Manufacturer	SIEMENS
MPN / Reference	3RA2437-8XH32-1NB3
Catalog number	24378
Category	Combination of contactors
Minimum order	1 Pcs
Document ID	EO-A041DD9FFB
Generated	2026-08-06

Product Overview

Contactor assembly for star-delta (wye-delta) start, AS-i AC-3, 55 kW/400 V, 20-33 V AC/DC 3-pole, Size S2 Screw terminal Electrical and mechanical interlock 3 NO + 3 NC integrated

STAR-TRIANGLE, SIZE S2, WITH ASI-I 115A, AC-3, 55KW / 400V , 20-33V AC / DC, 3NA+3NC INTEGRATED, SCREW TERMINALS, ENCLV. ELECTRICAL AND MECHANICAL. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors**

Additional Product Information

Technical data

Contactor assembly for star-delta (wye-delta) start, AS-i AC-3, 55 kW/400 V, 20-33 V AC/DC 3-pole, Size S2 Screw terminal Electrical and mechanical interlock 3 NO + 3 NC integrated

product brand name SIRIUS

product designation Contactor assembly for star-delta (wye-delta) start

product type designation 3RA24

manufacturer's article number

? 1 of the supplied contactor 3RT2037-1NB30-0CC0

? 2 of the supplied contactor 3RT2037-1NB30

? 3 of the supplied contactor 3RT2035-1NB30

? of the supplied RS assembly kit 3RA2933-2BB1

? of the supplied function module for communication 3RA2712-1CA00

General technical data

size of contactor S2

product extension auxiliary switch No

shock resistance at rectangular impulse

? at DC 7.7g / 5 ms, 4.5g / 10 ms

shock resistance with sine pulse

? at DC 12g / 5 ms, 7g / 10 ms

mechanical service life (switching cycles)

? of contactor typical 10 000 000

? of the contactor with added auxiliary switch block typical 10 000 000

reference code according to IEC 81346-2 Q

Substance Prohibitance (Date) 10/01/2014

Ambient conditions

installation altitude at height above sea level maximum 2 000 m

ambient temperature

? during operation -25 ... +60 °C

? during storage -55 ... +80 °C

Main circuit

number of poles for main current circuit 3

number of NO contacts for main contacts 3

number of NC contacts for main contacts 0

operating voltage at AC-3 rated value maximum 690 V

operational current at AC-3

? at 400 V rated value 115 A

operating power

? at AC-...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA2437-8XH32-1NB3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.